

Town of Chichester

Office of the Planning Board

54 Main Street Chichester, New Hampshire 03258 (603) 798-5350 Fax (603) 798-3170

Planning Board Chairman
Stan Brehm
Vice Chairman
Michael Williams

Administration
Kristy Barnouski, Secretary

Notice of Public Meeting Thursday April 9, 2020 6:30 PM Via Teleconference

AGENDA

PUBLIC HEALTH NOTICE: The Town of CHICHESTER is scheduled to hold a public hearing on APRIL 9, 2020 at 6:30PM regarding the topic's below:

- 1. Call to order at 6:30 pm.
- 2. Approve Minutes from previous meeting
- 3. Site Plan Review- Amendment for DBU Construction, Inc. of building and site to approved Site Plan, Map 4 Lot 151, 10 Dover Road. To construct a contractor yard and garage for equipment storage.
- 4. Site Plan Review- Mal-Mar, LLC-Bobcat, Map 4 Lot 150-C & Map 4 Lot 150-E. An expansion of the site is proposed to regrade and create additional storage area for the exiting retail sales business.
- 5. Site Plan Review- Amendment for Chichester Commons, LLC. Map 4 Lot 161-A & Map 4 Lot 161 114/114A Dover Road. To amend previous Planning Board approval for 14-unit (11-one bedroom and 3-two bedroom) project to reduce to 13 unit (9-one bedroom and 4-two bedroom). Total bedroom count of 17 to remain the same.

IN LIGHT OF THE COVID 19 (CORONA VIRUS) SOCIAL DISTANCING ADVICE MADE BY THE GOVERNOR AND CDC, THE TOWN OF CHICHESTER FOLLOWING A DECLARATION OF EMERGENCY BY THE PLANNING BOARD CHAIRPERSON, IS PROVIDING A MEETING PARTICIPATION VIA TELEPHONE CONFERENCE FOR YOUR SAFETY.

If you would like to participate in the telephone conference, please call this number from home: **+1 253 215 8782** and enter this code: **Meeting ID: 274 084 386 & Password: 462192**. Follow along using a digital copy from our website at: ChichesterNH.org. We will also be streaming the meeting as a webinar which you join by going to this link: https://zoom.us/j/931331372?pwd=bXIDNmhpK0p6cU5sTIB5V09IYVJxZz09

Please Call Kristy Barnouski with any questions or concerns @ 798-5350 EXT 201 or Email: KBarnouski@ChichesterNH.org

CHICHESTER PLANNING BOARD

MAR 1 2 2020

SITE PLAN REVIEW APPLICATION

CARAGORE C

Owner of Record: _	DBU CONSTRUCTION	N, INC Date I	Received:
Map Number: 4	Lot Number: _151F	ee Paid:	Check Number:
Address: PO BO	(984, EPSOM, NH 032	234	
Daytime Phone Nun	nber: <u>603-736-9100</u>	_ Evening Phone	Number:
Prepared by: ROK	EH CONSULTING, LL	C JON ROKEH	<u>L</u>
Address: 89 KING	ROAD, CHICHESTER,	NH	
Daytime Phone Nun	nber:603-387-8688	_ Evening Phone	Number:
1. Road Location:	NH RTE 2, 202, & 9 A	KA DOVER RC	DAC
2. Property Located	in a CU zor	ne.	
3. Land is in open sp	pace (current use):	YES; X N	O
4. Area of entire trac feet)	et: 28.98 (acres).	Portion to b	e utilized: 11 (acres or square
5. Describe planned	use:		
STORAGE. C	GARAGE WILL BE SEF	RVICED BY SER	RAGE FOR EQUIPMENT PTIC AND WELL. DRAINAGE, D UTILITIES ARE PROPOSED.
Chichester and the L	s that he/she is familiar wi waws of the State of New lion, has complied with the	Hampshire govern	Regulations of the Town of ning site plan review, and in
		3-12-202	20
Property Owner or A	Applicant	Date	

Town of Chichester

Planning Board 54 Main Street Chichester, NH 03258

PERMISSION TO INSPECT FORM

I, ADAM TOWNE	, property owner of Map 4 Lot 151-1 on
DOVER ROAD	, in the town of Chichester, NH do hereby grant my permission for
the Town Engineer to ins	spect site improvements or plans when the Chichester Planning Board
requests.	
I understand that the cost	of the employment of said engineer for inspection(s), test(s), or review
shall be paid by me.	
	3-12-20
Signature of Owner	Date
Witness	Date

Chichester Planning Board Site Plan Review Checklist


In cases where not all items are applicable, draw a line through the items.

APPLICABLE (Y/N) X	INCLUDED (Y/N)	INITIALS	1	Thurs and a fell and the first the state of
			1.	Three copies of the completed application and checklist
X			2.	Site plan: 22" by 34" sheet size maximum,
				scale not less than 1" =100', match lines
				where needed, boundaries, water courses &
				bodies of water, trees and other vegetation,
				topography at 2' intervals to USGS datum,
				existing and proposed contours and finished
				grade elevations and other pertinent features, date, title, graphic scale, north arrow,
				location map, name & address of
				developer/applicant, designer/engineer,
				owner of record. On mylar sufficient to
v				record.
X			3.	List of names and addresses of abutters and
				owners of land within 200' of any property
Х			4	line. (YOU MAY NOT ABUT YOURSELF)
X			4. 5.	The appropriate fee
THOUSE MARKET THE STATE OF THE		***************************************	٦.	Plan of all buildings depicting their type, size, and location (setbacks)
Χ			6.	An elevation view or photo of all buildings
X			7.	Layout of off-street parking and loading
X			8.	Ingress-egress of site and depiction of streets
				both within and adjacent to site
X			9.	Solid waste disposal facilities
	-		10.	Location; size, and design of signs and
Χ			11.	advertising or instructional devices Location, type, direction, and illuminated
			ii,	area of outside lighting
Χ			12.	Other required exhibits or data, any permits
				specific to site.
			13.	Permanent first floor elevation of proposed
X				buildings
			14.	Existing water supply and sewage disposal
				facilities on the site and within 200' of the
				site, proposed water and sewage facilities, and provisions for expansion of water and
				sewage facilities
Χ			15.	Location, elevation, and layout of surface
			- •	drainage facilities
X			16.	Existing and proposed landscaping and open
V				space areas and treatment
X			17.	Gas, electric, telephone, CATV utility lines

X X		Boundry survey shown Description or depiction of proposed
		grading, filling, or other site preparation
X	 20.	Existing and proposed buffers
X	 21.	Existing and proposed screening
X	 22.	Sidewalks, access, loading & parking
X	 23.	Erosion and sedimentation control plan
X	 24.	Flood plain areas
X	 25.	Town Engineer authorization
X	26.	Wetlands Setbacks.

SITE DEVELOPMENT PLANS

DOVER ROAD- CHICHESTER, NH



NOTES:

1.) THE SUBJECT PARCEL IS LOT 151 ON THE TOWN OF CHICHESTER TAX MAP 4. THE OWNER OF RECORD IS D.B.U. CONSTRUCTION, INC. OF PO BOX 984, EPSOM, NEW HAMPSHIRE 03038. SEE MCRD V. 3599 P. 869.

2.) THE SUBJECT PARCEL IS ZONED CI/MF, R & OSW. MINIMUM LOT SIZE IS 2 ACRES. MINIMUM LOT FRONTAGE = 200'. SETBACKS ARE AS FOLLOWS: FRONT = 40' MIN. (90' FROM CENTERLINE OF ROUTE 4, 202 & 9), SIDE = 15' AND REAR = 15', ALL SUBJECT TO EXACT USE AND ZONE. THE SETBACKS SHOWN ARE FOR REFERENCE ONLY AND NEED TO BE VERIFIED WITH THE ZONING COMPLIANCE OFFICER.

3.) THIS PLAN IS THE RESULT OF AN ACTUAL FIELD SURVEY PERFORMED BY THIS OFFICE IN AUGUST TO DECEMBER OF 2018. I, JOSEPH M. WICHERT, NHLLS #783, CERTIFY THAT THE WORK WAS PREPARED BY ME OR THOSE UNDER MY DIRECT SUPERVISION.

4.) THE INTENT OF THIS PLAN IS TO SHOW THE BOUNDARY OF THE SUBJECT PARCEL AND THE CURRENT CONDITIONS THEREON.

5.) THE SUBJECT PARCEL IS IN ZONE X (AREAS DETERMINED TO BE OUTSIDE THE 0.2% ANNUAL CHANCE FLOODPLAIN) AS SHOWN ON THE FLOOD INSURANCE RATE MAP, MERRIMACK COUNTY, NEW HAMPSHIRE, MAP NUMBER 33013C0557E, EFFECTIVE DATE APRIL 19, 2010.

6.) THE VERTICAL DATUM IS NAVD 1988 AND THE HORIZONTAL DATUM IS NHSPC 1983/2011. THE DATUM WERE ESTABLISHED USING STATIC GPS OBSERVATIONS PERFORMED BY THIS OFFICE IN AUGUST OF 2018.

7.) THE UTILITY INFORMATION SHOWN IS BASED ON THE ABOVE GROUND LOCATION OF VISIBLE UTILITIES, THE CONTRACTOR NEEDS TO FIELD VERIFY ALL UTILITIES PRIOR TO ANY CONSTRUCTION. THIS OFFICE DOES NOT GUARANTEE THE LOCATION AND ACCURACY OF THE UTILITY DATA. DIG SAFE SHALL BE CONTACTED 72 HOURS PRIOR TO COMMENCING ANY CONSTRUCTION (811).

8.) THE PURPOSE OF THE PLAN SET IS TO SHOW THE PROPOSED IMPROVEMENTS FOR A COMMERCIAL DEVELOPEMENT ON THE SUBJECT PARCEL. DRAINAGE, GRADING, UTILITIES, AND PARKING LAYOUTS HAVE BEEN INCLUDED.

9.) THE PROPOSED PROJECT WILL BE CONSTRUCTED IN THREE PHASES PER NHDES AOT REQUIREMENTS. PHASE I WILL CONSIST OF THE COMMERCIAL FRONTAGE SITE ON NH RT 4. PHASE II WILL CONSIST OF THE PROPOSED OFFICE AND SHOP AREA ALONG WITH ASSOCIATED DRAINAGE AND PHASE III WILL BE THE CONTRACTOR YARD TO THE NORTHEAST. EACH PHASE MUST BE STABILIZED BEFORE ADVANCING TO A SUCCESSIVE PHASE.

LIST OF DRAWINGS

DWG NO.	DESCRIPTION
1	COVER SHEET
2,3	EXISTING CONDITIONS / BOUNDARY PLAN
4	OVERALL SITE AND GRADING PLAN
5, 6, 7	GRADING DRAINAGE EROSION CONTROL PLAN
8 ,9, 10, 11	LANDSCAPING LIGNTING PLANS
12,13,14,15,16	PARKING LOT DRIVE PROFILES
17, 18,19,20,21,22,23	CONSTRUCTION & EROSION CONTROL DETAILS

NOTE:

1. ALL MATERIALS AND METHODS OF CONSTRUCTION SHALL CONFORM TO THE TOWN OF CHICHESTER REGULATIONS AND THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", LATEST EDITION.

2. ELEVATIONS ARE BASED ON NAVD 1988 DATUM.

3. PHYSICAL EVIDENCE OF EXISTING UTILITIES WERE LOCATED ON THE GROUND HOWEVER PRIOR TO ANY CONSTRUCTION IT IS THE CONTRACTOR'S RESPONSIBILITY TO CONTACT DIG-SAFE AND VERIFY ALL UNDERGROUND UTILITY LOCATIONS.





LIST OF ADDITIONAL CONSULTANTS

LAND SURVEYOR JOSEPH M. WICHERT, LLS INC 802 AMHERST STREEET MANCHESTER, NH 03104 Phone: (603) 647-4282

WETLANDS AND SOIL SCIENTIST AARON WECHSLER ASPEN ENVIRONMENTAL 41 LIBERTY HILL ROAD BUILDING 2, UNIT 201 HENNIKER, NH 03242 603) 848-5606

AF UNDER THE	PROVISIONS OF RSA 674:35 & 673:36
IN ACCORE	TER PLANNING BOARD DANCE OF A MAJORITY VOTE OF D APPROVED
CHAIR	
SECRETARY	DATE SIGNED:

CONTACT DIG SAFE 72 HOURS PRIOR TO CONSTRUCTION

THE LOCATION OF ANY UTILITY INFORMATION SHOWN ON THIS PLAN IS APPROXIMATE. ROKEH CONSULTING, LLC. MAKES NO CLAIM TO THE ACCURACY OR COMPLETENESS OF UTILITIES SHOWN. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ANY UTILITIES WHETHER THEY BE ABOVE OR BELOW GROUND. PRIOR TO ANY EXCAVATION ON SITE THE CONTRACTOR SHALL CONTACT DIG SAFE AT 1-800-DIG-SAFE.

AGENCY APPROVALS:

NHDOT - DRIVEWAY PERMIT APPR # NH DOT DRIVEWAY PERMIT NO. 05-089-0035

NHDES - WETLAND APPROVAL # 2019-00923

NHDES - ALTERATION OF TERRAIN APPROVAL # AOT-1631


Developer: **DBU CONSTRUCTION** PO Box 984 Epsom, NH 03234


COVER SHEET COMMERCIAL SITE PLAN TAX PARCEL 4 LOT 151 DOVER ROAD CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE


	REVISIONS			
DATE	DESCRIPTION	DWN BY	CK BY	R
3-12-20	EDITS TO CONTRACTOR YARD LAYOUT	JR	JR	170
				89
				PH
		· —		


okeh Consulting, LLC KING ROAD, CHICHESTER, NH H: 603-387-8688


SCALE: 1" = 100"DATE: JANUARY 14, 2019 DR. BY: JR CK. BY: JR JOB NO. _____ SHEET NO. 1 OF 23




















Schedule											
Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens Per Lamp	Light Loss Factor	Wattage
	W	10	Lithonia Lighting	KAXW LED P2 40K R4 MVOLT	KAXW LED, PERFORMANCE PACKAGE 2, 4000K, TYPE 4, 120- -277V; mounted at 18ft	LED	1	KAXW_LED_P2_ 40K_R4_MVOLT .ies	6284	0.9	49
	В3	4	Lithonia Lighting	RSX1 LED P2 40K R3 MVOLT RPA DDBXD	RSX Area Fixture Size 1 P2 Lumen Package 4000K CCT Type R3 Distribution; mounted at 20ft (18ft pole on 2ft base)	LED	1	RSX1_LED_P2_ 40K_R3.ies	9843	0.9	72.95



LIGHT POLE BASE

NOT TO SCALE





Developer:
DBU CONSTRUCTION
PO Box 984
Epsom, NH 03234

LIGHTING PLAN

COMMERCIAL SITE PLAN

TAX PARCEL 4 LOT 151

DOVER ROAD

CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

PEVISIONS

DATE DESCRIPTION DWN BY CK BY

4-4-19 EDITS PER PLANNING BOARD JR JR

5-20-19 EDITS PER AOT COMMENTS JR JR

6-17-19 EDITS TO DRIVES PER NHDOT COMMENTS JR JR

6-19-19 EDITS PER AOT COMMENTS BT JR


Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688 SCALE: 1" = 20"


DATE: DECEMBER 7, 2018

DR. BY: JR CK. BY: JR

JOB NO. _____

SHEET NO. 9 OF 14





GENERAL LANDSCAPE NOTES:
1. NO PLANTINGS CONFLICT WITH SNOW STORAGE AREAS.

- 2. NO LANDSCAPING CONFLICTS WITH SIGHT DISTANCE.
- 1 PERIMETER TREE / 20 FEET OF PARKING PERIMETER: 300 LF/20 = 15 TREES REQUIRED (22 PERIMETER TREES PROVIDED)
- 4. 1 INTERNAL TREE / 15 PARKING SPACES: 58 SPACES / 15 = 3.8 REQUIRED (6



Developer:
DBU CONSTRUCTION
PO Box 984
Epsom, NH 03234

LANDSCAPE PLAN

COMMERCIAL SITE PLAN

TAX PARCEL 4 LOT 151

DOVER ROAD

CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

	REVISIONS		
DATE	DESCRIPTION	DWN BY	CK BY
3-12-20	EDITS TO CONTRACTOR YARD LAYOUT	JR	_JR
<u>3-12-20</u>	EDITS TO CONTRACTOR YARD LAYOUT		

Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688 SCALE: 1" = 20"

DATE: DECEMBER 7, 2018


DR. BY: JR CK. BY: JR

JOB NO. _____

SHEET NO. 10 OF 23

LIGHT	POLF	RASI

Schedule											
Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens Per Lamp	Light Loss Factor	Wattage
	W	10	Lithonia Lighting	KAXW LED P2 40K R4 MVOLT	KAXW LED, PERFORMANCE PACKAGE 2, 4000K, TYPE 4, 120- -277V; mounted at 18ft	LED	1	KAXW_LED_P2_ 40K_R4_MVOLT .ies	6284	0.9	49
	В3	4	Lithonia Lighting	RSX1 LED P2 40K R3 MVOLT RPA DDBXD	RSX Area Fixture Size 1 P2 Lumen Package 4000K CCT Type R3 Distribution; mounted at 20ft (18ft pole on 2ft base)	LED	1	RSX1_LED_P2_ 40K_R3.ies	9843	0.9	72.95



Developer: DBU CONSTRUCTION PO Box 984 Epsom, NH 03234 LIGHTING PLAN
COMMERCIAL SITE PLAN
TAX PARCEL 4 LOT 151
DOVER ROAD
CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

	REVISIONS		
DATE	DESCRIPTION	DWN BY	CK BY
3-12-20	EDITS TO CONTRACTOR YARD LAYOUT	JR	JR


Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688 SCALE: 1" = 20"


DATE: DECEMBER 7, 2018


DR. BY: JR CK. BY: JR

JOB NO. _____

SHEET NO. 11 OF 23














S2-36*BCB 1045 1	2 + 3 0 · 3 · 3 · 3 · 3 · 3 · 3 · 3 · 3 · 3
187+00 188+00 8 189+00 190+00 191+00 193+00 193+00 185 1940 00 185 185 185 185 185 185 185 185 185 185	195±00 195±00

Developer:
DBU CONSTRUCTION
PO Box 984
Epsom, NH 03234

SITE DISTANCE PROFILES

COMMERCIAL SITE PLAN

TAX PARCEL 4 LOT 151

DOVER ROAD

CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

	REVISIONS		
DATE	DESCRIPTION	DWN BY	CK BY
4-4-19	EDITS PER PLANNING BOARD	JR	JR
5-20-19	EDITS PER AOT COMMENTS	JR	JR
6-17-19	EDITS TO DRIVES PER NHDOT COMMENTS	JR	JR
9-10-19	EDITS TO DRIVES PER NHDOT COMMENTS	JR	JR


Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688 SCALE: 1" = 40"


DATE: JANUARY 14, 2019

DR. BY: JR CK. BY: JR

JOB NO. _____


SHEET NO. 14 OF 23







CONNECTOR ROAD



CB 2 IS TO BE INSTALLED AT THE LOCATION OF THE EXISTING OUTLET (HEADER TO BE REMOVED), AND ALL ADDITIONAL LENGTHS OF 18" RCP WILL BE OWNED AND MAINTAINED BY THE DRIVEWAY PERMITTEE. THE ANNULAR SPACE SHOULD BE SEALED/GROUTED.



Developer:
DBU CONSTRUCTION
PO Box 984
Epsom, NH 03234

CONNECTION ROAD PROFILES

COMMERCIAL SITE PLAN

TAX PARCEL 4 LOT 151

DOVER ROAD

CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

	REVISIONS		
DATE	DESCRIPTION	DWN BY	CK BY
4-4-19	EDITS PER PLANNING BOARD	JR	JR
5-20-19	EDITS PER AOT COMMENTS	JR	JR
6-17-19	EDITS TO DRIVES PER NHDOT COMMENTS	JR	JR
<u>8-19-19</u>	EDITS TO DRIVES PER NHDOT COMMENTS	JR	JR


Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688 SCALE: 1" = 40"


DATE: JANUARY 14, 2019


DR. BY: JR CK. BY: JR

JOB NO. _____

SHEET NO. 16 OF 23







BLASTING BMP'S

NOTE: IF GREATER THAN 5000 CUBIC YARD OF BLAST ROCK WILL BE GENERATED, A GROUNDWATER MONITORING PROGRAM MUST BE DEVELOPED AND SUBMITTED TO NHDES.

A. Best Management Practices for Blasting. All activities related to blasting shall follow Best Management Practices (BMPs) to prevent contamination of groundwater including preparing, reviewing and following an approved blasting plan; proper drilling, explosive handing and loading procedures; observing the entire blasting procedures; evaluating blasting performance; and handling and storage of blasted rock.

- (1) Loading practices. The following blasthole loading practices to minimize environmental effects shall be followed:
 - (a) Drilling logs shall be maintained by the driller and communicated directly to the blaster. The logs shall indicate depths and lengths of voids, cavities, and fault zones or other weak zones encountered as well as groundwater conditions.
 - (b) Explosive products shall be managed on-site so that they are either used in the borehole, returned to the the delivery vehicle, or placed in secure containers for off-site disposal.
 - (c) Spillage around the borehole shall either be placed in the borehole or cleaned up and returned to an appropriate vehicle for handling or placement in secured containers for off-site disposal.
 - (d) Loaded explosives shall be detonated as soon as possible and shall not be left in the blastholes overnight, unless weather or other safety concerns reasonably dictate that detonation should be postponed.
 - (e) Loading equipment shall be cleaned in an area where wastewater can be properly contained and handled in a manner that prevents release of contaminants to the environment.
 - (f) Explosives shall be loaded to maintain good continuity in the column load to promote complete detonation. Industry accepted loading practices for priming, stemming, decking and column rise need to be attended to.
- **(2) Explosive Selection.** The following BMPs shall be followed to reduce the potential for groundwater contamination when explosives are used:
 - (a) Explosive products shall be selected that are appropriate for site conditions and safe blast execution.
 - (b) Explosive products shall be selected that have the appropriate water resistance for the site conditions present to minimize the potential for hazardous effect of the product upon groundwater.
- (3) **Prevention of Misfires.** Appropriate practices shall be developed and implemented to prevent misfires.
- (4) Muck Pile Management. Muck piles (the blasted pieces of rock) and rock piles shall be managed in a manner to reduce the potential for contamination by implementing the following measures:
 - (a) Remove the muck pile from the blast area as soon as reasonably possible.
 - (b) Manage the interaction of blasted rock piles and stormwater to prevent contamination of water supply wells or surface water.

Page 2 of 3

- (5) Spill Prevention Measures and Spill Mitigation. Spill prevention and spill mitigation measures shall be implemented to prevent the release of fuel and other related substances to the environment. The measures shall include at a minimum:
 - (a) The fuel storage requirements shall include:
 - 1. Storage of regulated substances on an impervious surface.
 - 2. Secure storage areas against unauthorized entry.3. Label regulated containers clearly and visibly.
 - 4. Inspect storage areas weekly.
 - 5. Cover regulated containers in outside storage areas.
 - 6. Wherever possible, keep regulated containers that are stored outside more than 50 feet from surface water and storm drains, 75 feet from private wells, and 400 feet from public wells.
 - 7. Secondary containment is required for containers containing regulated substances stored outside, except for on premise use heating fuel tanks, or aboveground or underground storage tanks otherwise regulated.
- (b) The fuel handling requirements shall include:
- 1. Except when in use, keep containers containing regulated substances closed and sealed.
- 2. Place drip pans under spigots, valves, and pumps.
- 3. Have spill control and containment equipment readily available in all work
- 4. Use funnels and drip pans when transferring regulated substances.5. Perform transfers of regulated substances over an impervious surface.
- (c) The training of on-site employees and the on-site posting of release response information describing what to do in the event of a spill of regulated substances.
- (d) Fueling and maintenance of excavation, earthmoving and other construction related equipment will comply with the regulations of the New Hampshire Department of Environmental Services [note these requirements are summarized in WD-DWGB-22-6 Best Management Practices for Fueling and Maintenance of Excavation and Earthmoving Equipment" or its successor document. (see

http://des.nh.gov/organization/commissioner/pip/factsheets/dwgb/documents/dwgb-22-6.pdf)

Page 3 of 3



Developer:
DBU CONSTRUCTION
PO Box 984
Epsom, NH 03234

CONSTRUCTION DETAILS

COMMERCIAL SITE PLAN

TAX PARCEL 4 LOT 151

DOVER ROAD

CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

	REVISIONS	GRATE H20 LOADING	G	
DATE	DESCRIPTION		BY CK BY	1.
6-26-19	EDITS PER AOT COMMENTS	BT	JR	
				8
				∦ F


Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688 SCALE: 1" = 50"


DATE: JANUARY 14, 2019

DR. BY: JR CK. BY: JR

JOB NO. _____

SHEET NO. 20 OF 23





TYPICAL CROSS SECTION SUBDRAINS TO BE TIED TO HEADWALLS OR DRAINAGE DITCHES CHAMBER SUBDRAIN DETAIL TYPICAL


INSPECTION & MAINTENANCE


STEP 1) INSPECT ISOLATOR ROW FOR SEDIMENT A. INSPECTION PORTS (IF PRESENT)


A 1. REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN

- A.2. REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED A.3. USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
- A.4. LOWER A CAMERA INTO ISOLATOR ROW FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL) A.5. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- B. ALL ISOLATOR ROWS B.1. REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW
- B.2. USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW THROUGH OUTLET PIPE
- MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY ii) FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
- B.3. IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW USING THE JETVAC PROCESS A. A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45" (1.1 m) OR MORE IS PREFERRED
- APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS. STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

- 1. INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- 2. CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY







90.0" (2286 mm)

22.5"

(571 mm)


INSTALLED


ACTUAL LENGTH

(1143 mr (1956 mm)

END CAP STORAGE

MINIMUM INSTALLED STORAGE^{*}





NOMINAL CHAMBER SPECIFICATIONS SIZE (W X H X INSTALLED LENGTH CHAMBER STORAGE MINIMUM INSTALLED STORAGE*


77.0" X 45.0" X 86.0" (1956 mm X 1143 mm X 2184 mm) 109.9 CUBIC FEET 178.9 CUBIC FEET (5.06 m³)

77.0" X 45.0" X 22.5" (1956 mm X 1143 mm X 571 mm) 14.9 CUBIC FEET 46.0 CUBIC FEET

*ASSUMES 12" (305 mm) STONE ABOVE, 9" (229 mm) STONE FOUNDATION AND BETWEEN CHAMBERS, 12" (305 mm) STONE PERIMETER IN FRONT OF END CAPS AND 40% STONE POROSITY

STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B" STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"

PART#	STUB	В	С
MC3500IEPP06T	6" (150 mm)	33.21" (844 mm)	
MC3500IEPP06B	0 (130 11111)		0.66" (17 mm)
MC3500IEPP08T	8" (200 mm)	31.16" (791 mm)	
MC3500IEPP08B	0 (200 111111)		0.81" (21 mm)
MC3500IEPP10T	10" (250 mm)	29.04" (738 mm)	
MC3500IEPP10B	10 (230 111111)		0.93" (24 mm)
MC3500IEPP12T	12" (300 mm)	26.36" (670 mm)	
MC3500IEPP12B	12 (300 11111)		1.35" (34 mm)
MC3500IEPP15T	15" (375 mm)	23.39" (594 mm)	
MC3500IEPP15B	15 (3/5111111)		1.50" (38 mm)
MC3500IEPP18TC	18" (450 mm)	20.03" (509 mm)	
MC3500IEPP18BC	10 (430111111)		1.77" (45 mm)
MC3500IEPP24TC	24" (600 mm)	14.48" (368 mm)	
MC3500IEPP24BC	24 (000 111111)		2.06" (52 mm)
MC3500IEPP30BC	30" (750 mm)		



25.7"




NOTE: ALL DIMENSIONS ARE NOMINAL

CUSTOM PRECORED INVERTS ARE AVAILABLE UPON REQUEST. INVENTORIED MANIFOLDS INCLUDE 12-24" (300-600 mm) SIZE ON SIZE AND 15-48" (375-1200 mm) ECCENTRIC MANIFOLDS. CUSTOM INVERT LOCATIONS ON THE MC-3500 END CAP CUT IN THE FIELD ARE NOT RECOMMENDED FOR PIPE SIZES GREATER THAN 10" (250 mm)

THE INVERT LOCATION IN COLUMN 'B' ARE THE HIGHTEST POSSIBLE FOR THE PIPE SIZE.

MC-3500 TECHNICAL SPECIFICATION

SEE ADS SHOP DRAWINGS FOR **UNDERGROUND DETENTION DETAILS** AND CONSTRUCTION





OUTLET STRUCTURE DETAIL


Developer: **DBU CONSTRUCTION** PO Box 984 Epsom, NH 03234

STORMTECH DETAILS COMMERCIAL SITE PLAN TAX PARCEL 4 LOT 151 DOVER ROAD CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

REVISIONS GRATE H20 LOADING DATE DESCRIPTION DWN BY CK BY

Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688

SCALE: 1" = 40"DATE: JANUARY 14, 2019 DR. BY: JR CK. BY: JR JOB NO. _____ SHEET NO. 21 OF 23



THE EXIT SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY, WHEN THE CONTROL PAD BECOMES INEFFECTIVE, THE STONE SHALL BE REMOVED ALONG WITH THE COLLECTED SOIL MATERIAL, REGRADED ON SITE, AND STABILIZED, THE ENTRANCE SHALL THEN BE RECONSTRUCTED.

- 2. THE CONTRACTOR SHALL SWEEP THE PAVEMENT AT EXITS WHENEVER SOIL MATERIALS ARE TRACKED ONTO THE
- 3. WHEN WHEEL WASHING IS REQUIRED, IT SHALL BE CONDUCTED ON AN AREA STABILIZED WITH AGGREGATE, WHICH DRAINS INTO AN APPROVED SEDIMENT-TRAPPING DEVICE. ALL SEDIMENT SHALL BE PREVENTED FROM ENTERING STORM DRAINS, DITCHES, OR WATERWAYS.

- CONSTRUCTION SPECIFICATIONS
 4. ONLY CONSTRUCTION TRAFFIC LEAVING THE SITE IS REQUIRED TO USE THE TEMPORARY STABILIZED EXIT. CONSIDER PROVIDING A SEPARATE, UNPROTECTED, ENTRANCE FOR TRAFFIC ENTERING THE SITE. THIS WILL INCREASE THE LONGEVITY OF THE STABILIZED EXIT BY ELIMINATING HEAVY LOADS ENTERING THE SITE AND REDUCING THE TOTAL
- 5. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND, AND REPAIR AND/OR MAINTENANCE OF ANY MEASURES USED TO TRAP SEDIMENT.
- 6. STONE FOR A TEMPORARY CONSTRUCTION EXIT SHALL BE 3 INCH STONE, RECLAIMED STONE, OR RECYCLED CONCRETE
- 7. THE MINIMUM LENGTH OF THE PAD SHALL BE 75 FEET, EXCEPT THAT THE MINIMUM LENGTH MAY BE REDUCED TO 50 FEET IF A 3-INCH TO 6-INCH HIGH BERM IS INSTALLED AT THE ENTRANCE OF THE PROJECT SITE.
- 8. THE THICKNESS OF THE STONE FOR THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 6 INCHES. 9. THE WIDTH OF THE ENTRANCE SHALL NOT BE LESS THAN THE FULL WIDTH OF THE EXIT OR 10 FEET, WHICH EVER IS
- 10. GEOTEXTILE FILTER CLOTH SHALL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING THE STONE.
- 11. ALL SURFACE WATER THAT IS FLOWING TO OR DIVERTED TOWARD THE CONSTRUCTION EXIT SHALL BE PIPED BENEATH THE ENTRANCE. IF PIPING IS IMPRACTICAL, A BERM WITH 5:1 SLOPES THAT CAN BE CROSSED BY VEHICLES MAY BE SUBSTITUTED FOR THE PIPE.

TEMPORARY CONSTRUCTION EXIT

CONSTRUCTION SEQUENCES:

(THESE SEQUENCES TO APPLY FOR BOTH ROAD & LOT CONSTRUCTION)

NOTE: - ALL EROSION CONTROLS TO BE INSPECTED WEEKLY AND AFTER EVERY .5" OF RAINFALL.

AN ENVIRONMENTAL MONITOR MAY BE REQUIRED DUE TO THE POSSIBILITY OF A GREATER THAN 5 ACRES BEING DISTURBED PRIOR TO STABILIZATION. THE MONITOR SHALL ADHERE TO ALL REQUIREMENTS OF ENV-WQ 1505.03(D) AS NOTED BELOW.

- 1. PRIOR TO CONSTRUCTION INSTALL FABRIC SILTATION FENCING AS SHOWN ON PLAN
- CONSTRUCT TEMPORARY STABILIZED ENTRANCE, AND INSTALL OTHER APPROPRIATE SEDIMENT AND EROSION CONTROL. 2. CUT AND CLEAR ALL VEGETATION AND STUMPS FROM CUT SLOPES, PONDS, AND SWALE AREAS.
- 3. COMPLETE TEMPORARAY SEDIMENT BASINS AT POND LOCATIONS. CONSTRUCT BERMS AND SWALES TO DIRECT STORMWATER TO BASINS. SEDIMENT BASINS LOCATED WITHIN PROPOSED INFILTATION BASIN AREAS ARE TO BE CONSTRUCTED A MINIMUM OF 1' ABOVE THE FINAL BASIN FLOOR ELEVATION.
- 4. AN AREA IS CONSIDERED STABLE IF:
- A.) BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED; B.) A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED: A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE, OR RIP-RAP HAS BEEN INSTALLED; OR
- EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
- 5. CUT AND CLEAR ALL VEGETATION AND STUMPS FROM AREAS TO BE DISTURBED FOR THE CONSTRUCTION OF THE
- 6. REMOVE TOPSOIL AND OTHER ORGANIC MATERIALS FROM AREAS TO BE DISTURBED. ALL SUCH TOPSOIL REMOVED
- SHALL BE STOCKPILED FOR LATER USE. ALL STOCKPILES SHALL BE SEEDED AND MULCHED TO PREVENT LOSS DUE TO EROSION, AND ENCIRCLED WITH FABRIC SILT FENCE. WHEN CONSTRUCTION ACTIVITIES ARE TEMPORARILY CEASED FOR MORE THAN 21 DAYS. PERMANENTLY CEASED, OR SHUT DOWN FOR WINTER, THE CONTRACTOR SHALL LEAVE NO SLOPES STEEPER THAN 3;1 AND SHALL IMPLEMENT TEMPORARY LOAMING, SEEDING AND MULCHING. WHERE CONSTRUCTION ACTIVITIES HAVE BEEN SUSPENDED OUTSIDE THE GROWING SEASON ALL EXPOSED SOIL SHALL BE STABILIZED BY MULCHING, AND ALL SLOPES GREATER THAN 3:1 SHALL BE STABILIZED WITH NETTING & PINNING.
- 7. CONSTRUCT, CUT, AND FILL SLOPES. ALL CUT AND FILL SLOPES TO BE STABILIZED IMMEDIATELY AFTER CONSTRUCTION. ALL SLOPES GREATER THAN 3:1 TO BE STABILIZED WITH JUTE MATTING. ALL CUT AND FILL SLOPES SHALL BE SEEDED AND LOAMED WITHIN 72 HOURS OF ACHIEVING FINISH GRADE.
- 8. CONSTRUCT STORM DRAINAGE, AND OTHER UNDERGROUND UTILITIES. ALL SWALES TO BE PROTECTED WITH TEMPORARY EROSION CONTROL MEASURES SHOWN. ALL CATCH BASIN OPENINGS TO BE PROTECTED WITH BLOCK AND GRAVEL INLET SEDIMENT FILTERS AS SHOWN. SEDIMENT TRAPS AND/OR BASINS SHOULD BE USED UNTIL BASINS/PONDS ARE STABILIZED.
- 9. BEGIN TOP SOILING, SEEDING AND Mulching IMMEDIATELY AFTER COMPLETION OF EMBANKMENTS. TEMPORARY EROSION CONTROL / DIVERSION CHANNELS SHALL BE IMPLEMENTED WHERE REQUIRED TO PREVENT EROSION OF EMBANKMENTS. ANY EROSION OCCURRING SHALL BE REPAIRED IMMEDIATELY UPON DISCOVERY.
- 10. FINISH GRADING & PAVING. ALL ROADWAYS AND PARKING LOTS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISH GRADES.
- 11. ALL PAVED AREAS TO BE COMPLETED BY OCTOBER 15. ALL LANDSCAPED AREAS TO BE STABILIZED BY OCTOBER 15th, WITH HAY MULCH AND SEED.
- 12. COMPLETE PERMANENT SEEDING AND MULCHING OF ALL DISTURBED AREAS. ALL TEMPORARY EROSION CONTROL MEASURES TO REMAIN IN PLACE UNTIL A FULL VEGETATIVE COVER HAS BEEN ESTABLISHED ON ALL DISTURBED AREAS.
- 13. SILT FENCES AND HAY BALE BARRIERS TO BE REMOVED ONCE THE SITE HAS STABILIZED.

- 1. TEMPORARY SEEDING SHALL BE INSPECTED WEEKLY AND AFTER ANY RAINFALL EXCEEDING ½ INCH IN 24 HOURS ON ACTIVE CONSTRUCTION SITES. TEMPORARY SEEDING SHALL ALSO BE INSPECTED JUST PRIOR TO SEPTEMBER 15, TO ASCERTAIN WHETHER ADDITIONAL SEEDING IS REQUIRED TO PROVIDE STABILIZATION OVER THE WINTER PERIOD.
- 2. BASED ON INSPECTION, AREAS SHALL BE RESEEDED TO ACHIEVE FULL STABILIZATION OF EXPOSED SOILS. IF IT IS TOO LATE IN THE PLANTING SEASON TO APPLY ADDITIONAL SEED, THEN OTHER TEMPORARY STABILIZATION MEASURES SHALL
- 3. AT A MINIMUM, 85% OF THE SOIL SURFACE SHALL BE COVERED BY VEGETATION.
- 4. IF ANY EVIDENCE OF EROSION OR SEDIMENTATION IS APPARENT, REPAIRS SHALL BE MADE AND AREAS SHALL BE RESEEDED, WITH OTHER TEMPORARY MEASURES (E.G., MULCH) USED TO PROVIDE EROSION PROTECTION DURING THE PERIOD OF VEGETATION ESTABLISHMENT.

- 5. INSTALL NEEDED EROSION AND SEDIMENT CONTROL MEASURES SUCH AS SILTATION BARRIERS, DIVERSIONS, AND SEDIMENT TRAPS
- 6. GRADE AS NEEDED FOR THE ACCESS OF EQUIPMENT FOR SEEDBED PREPARATION, SEEDING, MULCH APPLICATION, AND MULCH ANCHORING.
- 7. RUNOFF SHALL BE DIVERTED FROM THE SEEDED AREA.
- 8. ON SLOPES 4:1 OR STEEPER, THE FINAL PREPARATION SHALL INCLUDE CREATING HORIZONTAL GROOVES PERPENDICULAR TO THE DIRECTION OF THE SLOPE TO CATCH SEED AND REDUCE RUNOFF.

9. STONES AND TRASH SHALL BE REMOVED SO AS NOT TO INTERFERE WITH THE SEEDING AREA.

- 10. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF 2 INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED.
- 11. IF APPLICABLE, FERTILIZER AND ORGANIC SOIL AMENDMENTS SHALL BE APPLIED DURING THE GROWING SEASON. - APPLY LIMESTONE AND FERTILIZER ACCORDING TO SOIL TEST RECOMMENDATIONS. IF SOIL TESTING IS NOT FEASIBLE ON SMALL OR VARIABLE SITES, OR WHERE TIMING IS CRITICAL, FERTILIZER MAY BE APPLIED AT THE RATE OF 600 POUNDS PER ACRE OR 13.8 POUNDS PER 1,000 SQUARE FEET OF LOW PHOSPHATE FERTILIZER1 (N-P2O5-K2O) OR EQUIVALENT. APPLY LIMESTONE (EQUIVALENT TO 50 PERCENT CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF 3 TONS PER ACRE (138 LB. PER 1,000 SQUARE FEET).
 - FERTILIZER SHALL BE RESTRICTED TO A LOW PHOSPHATE, SLOW RELEASE2 NITROGEN FERTILIZER WHEN APPLIED TO AREAS BETWEEN 25 FEET AND 250 FEET FROM A SURFACE WATER BODY. NO FERTILIZER EXCEPT LIMESTONE SHALL BE APPLIED WITHIN 25 FEET OF A SURFACE WATER BODY. THESE LIMITATIONS ARE REQUIREMENTS FOR ANY WATER BODY PROTECTED BY THE COMPREHENSIVE SHORELAND PROTECTION ACT.


12. SELECT SEED FROM RECOMMENDATIONS IN TABLE 4-1.

- 13. APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, DRILL, CULTIPACKER TYPE SEEDER OR HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). NORMAL SEEDING DEPTH IS FROM ¼ TO ½ INCH. HYDROSEEDING THAT INCLUDES MULCH MAY BE LEFT ON SOIL SURFACE. SEEDING RATES MUST BE INCREASED 10 % WHEN HYDROSEEDING.
- 14. TEMPORARY SEEDING SHALL TYPICALLY OCCUR PRIOR TO SEPTEMBER 15TH.
- 15. AREAS SEEDED BETWEEN MAY 15TH AND AUGUST 15TH SHALL BE COVERED WITH HAY OR STRAW MULCH, ACCORDING TO THE "TEMPORARY AND PERMANENT MULCHING" PRACTICE.
- 16. VEGETATED GROWTH COVERING AT LEAST 85% OF THE DISTURBED AREA SHALL BE ACHIEVED PRIOR TO OCTOBER 15TH. IF THIS CONDITION IS NOT ACHIEVED, IMPLEMENT OTHER TEMPORARY STABILIZATION MEASURES FOR OVERWINTER PROTECTION

TABLE 4-1. SE	EDING RECOMMENDATIONS	FOR TEMPORARY VEG	ETATION
SPECIES	PER ACRE BUSHELS	PER 1,000 FT2	REMARKS
	(BU) OR POUNDS (LBS)	
WINTER RYE			2 BU. OR 112 LBS. 2.5 LBS. BEST FOR FALL SEEDING. SEED FROM AUGUST 15 TO SEPTEMBER 15 FOR BEST COVER. SEED TO A DEPTH OF 1 INCH.
OATS			2.5 BU. OR 80 LBS. 2 LBS. BEST FOR SPRING SEEDINGS. SEED NO LATER THAN MAY 15 FOR SUMMER PROTECTION. SEED TO A DEPTH OF 1 INCH.
ANNUAL RYEGRASS			40 LBS. 1 LB. GROWS QUICKLY, BUT IS OF SHORT DURATION. USE WHERE APPEARANCES ARE IMPORTANT. SEED EARLY SPRING AND/OR BETWEEN AUGUST 15 AND SEPTEMBER 15. COVER THE SEED WITH NO MORE THAN 0.25 INCH OF SOIL.
PERENNIAL RYEGRASS TEN	IPORARY VE	GETATION	30 LBS. GOOD COVER WHICH IS LONGER LASTING THAN ANNUAL RYEGRASS. SEED BETWEEN APRIL 1 AND JUNE 1 AND/OR

- BETWEEN AUGUST 15 AND SEPTEMBER 15. MULCHING WILL ALLOW SEEDING THROUGHOUT THE GROWING SEASON. SEED TO A DEPTH OF APPROXIMATELY 0.5 INCH.

 14. REMOVE ACCUMULATIONS OF SEDIMENT FROM DRAINAGE STRUCTURES, MICROPOOL POND TO BE CLEANED OUT.
- LOAMED & MATTED AS NECESSARY UPON COMPLETION OF PROJECT. 15. THE MAXIMUM AMOUNT OF AREA ALLOWED TO BE DISTURBED & UNSTABILIZED AT ONE TIME IS 1.5 ACRES. ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS FROM INITIAL DISTURBANCE.
- 16. WINTER CONSTRUCTION NOTES:
- A.) DURING WINTER CONDITIONS, THE MAXIMUM ALLOWABLE DISTURBED AREA SHALL BE 0.5 ACRES. B.) ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MAXIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15th, OR WHICH ARE DISTURBED AFTER OCTOBER 15th, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.
- C.) ALL DITCHES AND SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15th, OR WHICH ARE DISTURBED AFTER OCTOBER 15th, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS. D.) AFTER OCTOBER 15th, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER
- SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER N.H.D.O.T. ITEM 304.3.
- 17. AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED: A.) BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED;
 - B.) A MINIMUM OF 85% VEGETATIVE GROWTH HAS BEEN ESTABLISHED;
 - C.) A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED; OR D.) EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
- 18. BASINS AND SWALES SHALL BE INSTALLED EARLY IN THE CONSTRUCTION SEQUENCE AND PRIOR TO ANY ROUGH GRADING OF THE SITE.
- 19. ALL DITCHES, SWALES AND BASINS SHALL BE STABILIZED PRIOR TO DIRECTING RUNOFF TO THEM.
- 20. LOT DISTURBANCE, OTHER THAN THAT SHOWN ON THE APPROVED PLANS, SHALL NOT OCCUR UNTIL AFTER THE ROADWAY AND ASSOCIATED DRAINAGE HAVE BEEN COMPLETED AND STABILIZED. INDIVIDUAL LOT DEVELOPMENT THAT IS PLANNED TO EXCEED 100,000 SQUARE FEET (OR 50,000 SQUARE FEET WITHIN THE CSPA) MAY REQUIRE A ALTERATION OF TERRAIN APPLICATION PRIOR TO LOT DEVELOPMENT.



CONSIDERATIONS

1. THIS PRACTICE IS INTENDED FOR USE IN AREAS OF CONCENTRATED FLOW, BUT MUST NOT BE USED IN STREAM CHANNELS

2. THE CHECK DAM MAY BE LEFT IN PLACE PERMANENTLY TO AVOID UNNECESSARY DISTURBANCE OF THE SOIL ON REMOVAL, BUT ONLY IF THE PROJECT DESIGN HAS ACCOUNTED FOR THEIR HYDRAULIC PERFORMANCE AND CONSTRUCTION PLANS CALL FOR THEM TO BE RETAINED.

3. IF IT IS NECESSARY TO REMOVE A STONE CHECK DAM FROM A GRASSLINED CHANNEL THAT WILL BE MOWED, CARE SHALL BE TAKEN TO ENSURE THAT ALL STONES ARE REMOVED. THIS INCLUDES STONE THAT HAS WASHED DOWNSTREAM.

MAINTENANCE REQUIREMENTS
4. CHECK DAMS SHALL BE INSPECTED AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL AND

5. INSPECTIONS SHALL VERIFY THAT THE CENTER OF THE DAM IS LOWER THAN THE EDGES. 6. EROSION CAUSED BY HIGH FLOWS AROUND THE EDGES OF THE DAM MUST BE CORRECTED IMMEDIATELY.

- 7. IF EVIDENCE OF SILTATION IN THE WATER IS APPARENT DOWNSTREAM FROM THE CHECK DAM, THE CHECK DAM SHALL BE INSPECTED AND ADJUSTED IMMEDIATELY.
- 8. CHECK DAMS SHALL BE CHECKED FOR SEDIMENT ACCUMULATION AFTER EACH SIGNIFICANT RAINFALL. SEDIMENT SHALL BE REMOVED WHEN IT REACHES ONE HALF OF THE ORIGINAL HEIGHT OR BEFORE.

9. CHECK DAMS SHALL BE INSTALLED BEFORE RUNOFF IS DIRECTED TO THE SWALE OR DRAINAGE DITCH.


- 10. THE MAXIMUM CONTRIBUTING DRAINAGE AREA TO THE DAM SHALL BE LESS THAN ONE ACRE.
- 11. THE MAXIMUM HEIGHT OF THE DAM SHALL BE 2 FEET.

NECESSARY REPAIRS SHALL BE MADE IMMEDIATELY.

- 12. THE CENTER OF THE DAM SHALL BE AT LEAST 6 INCHES LOWER THAN THE OUTER EDGES.
- 13. THE MAXIMUM SPACING BETWEEN THE DAMS SHALL BE SUCH THAT THE TOE OF THE UPSTREAM DAM IS AT THE SAME ELEVATION AS THE OVERFLOW ELEVATION OF THE DOWNSTREAM DAM.
- 14. STONE CHECK DAMS SHALL BE CONSTRUCTED OF A WELL-GRADED ANGULAR 2-INCH TO 3-INCH STONE. 3/4-INCH STONE ON THE UPGRADIENT FACE IS RECOMMENDED FOR BETTER FILTERING.
- 15. IF PROVIDED BY DESIGN AND CONSTRUCTION PLANS, LEAVE THE DAM IN PLACE PERMANENTLY.
- 18. TEMPORARY STRUCTURES SHALL BE REMOVED ONCE THE SWALE OR DITCH HAS BEEN STABILIZED: - IN TEMPORARY DITCHES AND SWALES, CHECK DAMS SHALL BE REMOVED AND THE DITCH FILLED IN WHEN IT IS NO LONGER NEEDED.
 - IN PERMANENT STRUCTURES, CHECK DAMS SHALL BE REMOVED WHEN A PERMANENT LINING HAS BEEN ESTABLISHED. IF THE PERMANENT LINING IS VEGETATION, THEN THE CHECK DAM SHALL BE RETAINED UNTIL THE GRASS HAS MATURED TO PROTECT THE DITCH OR SWALE. THE AREA BENEATH THE CHECK DAM MUST BE SEEDED

TEMPORARY STONE CHECK DAMS

NOT TO SCALE



1. INLET BARRIERS SHALL BE INSPECTED BEFORE AND AFTER EACH RAIN EVENT AND REPAIRED AS NEEDED.

- 2. SEDIMENT SHALL BE REMOVED AND THE STORM DRAIN SEDIMENT BARRIER RESTORED TO ITS ORIGINAL DIMENSIONS WHEN THE SEDIMENT HAS ACCUMULATED TO 1/2 THE DESIGN DEPTH OF THE BARRIER. REMOVED SEDIMENT SHALL BE DEPOSITED IN A SUITABLE AREA AND IN SUCH A MANNER THAT IT WILL NOT ERODE.
- 3. THE BARRIERS SHALL BE REMOVED AND THE AREA STABILIZED WHEN THE CONTRIBUTING DRAINAGE AREA HAS BEEN
- 4. ALL CATCH BASINS AND STORM DRAIN INLETS MUST BE CLEANED AT THE END OF CONSTRUCTION AND AFTER THE SITE HAS BEEN FULLY STABILIZED.

5. THE MAXIMUM CONTRIBUTING DRAINAGE AREA TO THE TRAP SHALL BE LESS THAN ONE ACRE.

- 6. THE INLET PROTECTION DEVICE SHALL BE CONSTRUCTED IN A MANNER THAT WILL FACILITATE CLEAN-OUT AND DISPOSAL OF TRAPPED SEDIMENTS AND MINIMIZE INTERFERENCE WITH CONSTRUCTION ACTIVITIES.
- 7. ANY RESULTANT PONDING OF STORMWATER MUST NOT CAUSE EXCESSIVE INCONVENIENCE OR DAMAGE TO ADJACENT

8. THE BLOCKS SHALL BE PLACED LENGTHWISE IN A SINGLE ROW AROUND THE PERIMETER OF THE INLET.


9. THE BLOCK ENDS SHALL ABUT ONE ANOTHER.

- 10. THE HEIGHT OF THE BARRIER CAN BE VARIED, DEPENDING ON DESIGN NEEDS, BY STACKING COMBINATIONS OF 4-INCH, 8-INCH AND 12-INCH WIDE BLOCKS. THE BARRIER OF BLOCKS AND GRAVEL FILTER SHALL BE A MINIMUM OF 12 INCHES HIGH AND NO MORE THAN 24 INCHES HIGH.
- 11. A HARDWARE CLOTH OR WIRE MESH SHALL BE PLACED OVER THE OPENINGS OF THE CONCRETE BLOCKS AND EXTEND AT LEAST 12 INCHES AROUND THE OPENING TO PREVENT AGGREGATE FROM BEING TRANSPORTED THROUGH THE OPENINGS IN THE BLOCKS. HARDWARE CLOTH OR COMPARABLE WIRE MESH WITH 1/2-INCH OPENINGS SHALL BE USED.
- 12. THE GRAVEL FILTER SHALL BE CLEAN COARSE AGGREGATE.
- 13. THE GRAVEL SHALL BE PLACED AGAINST THE WIRE AND ALONG THE OUTSIDE EDGES OF THE BLOCKS TO THE TOP OF THE
- 14. IF THE STONE FILTER BECOMES CLOGGED WITH SEDIMENT SO THAT IT NO LONGER ADEQUATELY PERFORMS ITS FUNCTION, THE STONE MUST BE PULLED AWAY FROM THE BLOCKS, CLEANED AND REPLACED.

5. MANUFACTURED SEDIMENT BARRIERS ARE NOW AVAILABLE THAT COULD BE FUNCTIONALLY EQUIVALENT TO THE BARRIERS LISTED ABOVE, THESE MEASURES ARE ACCEPTABLE AS LONG AS THEY ARE INSTALLED, USED, AND MAINTAINED AS SPECIFIED BY THE VENDOR OR MANUFACTURER, AND PREVENT SEDIMENT FROM ENTERING THE STORM DRAIN SYSTEM. IF SUCH PRODUCTS FAIL TO PERFORM THE REQUIRED SEDIMENT TRAPPING FUNCTION, THEY SHALL BE REMOVED AND REPLACED WITH AN EFFECTIVE ALTERNATIVE BARRIER.

TEMPORARY STORM DRAIN INLET PROTECTION

NOT TO SCALE SEDIMENT TRAPS AND SEDIMENT BASINS WILL BE INSPECTED FOR DEPTH OF SEDIMENT, AT A MINIMUM SEDIMENT WOULD BE REMOVED AND TRAP RESTORED TO ITS ORIGINAL SIZE WHEN SEDIMENT REACHES 1/2 OF THE ORIGINAL SIZE CLEAN AT 12"-CHECK RIP-RAP STONE 8" MIN. DIMENSION INLET DEPTH MARKER SEDIMENT TRAP 36" MIN. FENCE POST



1. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER, THEY SHALL BE OVERLAPPED BY 6 INCHES, FOLDED AND STAPLED.

2. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE.

EROSION CONTROL DETAILS COMMERCIAL SITE PLAN TAX PARCEL 4 LOT 151 **DOVER ROAD** CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE


DESCRIPTION DWN BY CK BY

REVISIONS

Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688

SCALE: 1" = 50"DATE: JANUARY 14, 2019 DR. BY: JR CK. BY: JR JOB NO. _____ SHEET NO. 22 OF 23

Developer: DBU CONSTRUCTION PO Box 984 Epsom, NH 03234



1. DURING THE GROWING SEASON (APRIL 15 - SEPTEMBER 15) USE MATS OR MULCH AND NETTING ON SLOPES 15% OR GREATER AND ANY DISTURBED SOIL WITHIN 100 FEET OF LAKES. STREAMS AND OOWETLANDS.

2. DURING THE LATE FALL AND WINTER (SEPTEMBER 15 - APRIL 15) USE HEAVY GRADE MATS ON ALL AREAS NOTED ABOVE PLUS USE LIGHTER GRADE MATS OR MULCH AND NETTING ON SLOPES GREATER THAN 8%. THERE MAY BE CASES WHERE MATS WILL BE NEEDED ON SLOPES FLATTER THAN 8%, DEPENDING ON SITE CONDITIONS AND THE LENGTH OF THE SLOPE.

3. INSTALL MATS AND STAPLE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.

4. ALL BLANKET AND MATS SHOULD BE INSPECTED WEEKLY DURING THE CONSTRUCTION PERIOD, AND AFTER ANY RAINFALL EVENT EXCEEDING 1/2 INCH IN A 24-HOUR PERIOD.

5. ANY FAILURE SHOULD BE REPAIRED IMMEDIATELY. IF WASHOUT OF THE SLOPE, DISPLACEMENT OF THE MAT, OR DAMAGE TO THE MAT OCCURS. THE AFFECTED SLOPE SHALL BE REPAIRED AND RESEDED, AND THE AFFECTED AREA OF MAT SHALL BE RE-INSTALLED OR REPLACED.

GRADE AND SHAPE AREA OF INSTALLATION.

7. REMOVE ALL ROCKS, CLODS, TRASH, VEGETATIVE OR OTHER OBSTRUCTIONS SO THAT THE INSTALLED BLANKETS WILL HAVE DIRECT CONTACT WITH THE SOIL.

8. PREPARE SEEDBED BY LOOSENING 2-3 INCHES OF TOPSOIL ABOVE FINAL GRADE.

9. INCORPORATE AMENDMENTS, SUCH AS LIME AND FERTILIZER, INTO SOIL ACCORDING TO SOIL TEST AND THE SEEDING

10. SEED AREA BEFORE BLANKET INSTALLATION FOR EROSION CONTROL AND RE-VEGETATION. SEEDING AFTER MAT INSTALLATION IS OFTEN SPECIFIED FOR TURF REINFORCEMENT APPLICATION. WHEN SEEDING PRIOR TO BLANKET INSTALLATION, ALL CHECK SLOTS AND OTHER AREAS DISTURBED DURING INSTALLATION MUST BE RESEEDED.

11. WHERE SOIL FILLING IS SPECIFIED, SEED THE MATTING AND THE ENTIRE DISTURBED AREA AFTER INSTALLATION AND PRIOR TO FILLING THE MAT WITH SOIL.

INSTALLING AND ANCHORING BLANKETS:
12. BLANKETS SHALL BE INSTALLED AND ANCHORED PER THE MANUFACTURER'S SPECIFICATIONS.

13. ENSURE COMPLETE CONTACT OF THE PROTECTION MATTING WITH THE SOIL.

14. BLANKETS SHALL BE INSTALLED ON SLOPES PER THE MANUFACTURER'S SPECIFICATIONS. IF THE MANUFACTURER'S INSTRUCTIONS DIFFER FROM THOSE LISTED BELOW, THE MANUFACTURER'S INSTRUCTIONS SHOULD BE FOLLOWED.

15. BEGIN AT THE TOP OF THE SLOPE BY ANCHORING THE BLANKET IN 6" DEEP X 6" WIDE TRENCH. BACKFILL AND COMPACT

16. ROLL THE BLANKETS (A.) DOWN OR (B.) HORIZONTALLY ACROSS THE SLOPE

17. THE EDGES OF PARALLEL BLANKETS MUST BE STAPLED WITH APPROXIMATELY 6" OVERLAP

18. WHEN BLANKETS MUST BE SPLICED DOWN THE SLOPE, PLACE BLANKETS END OVER END (SHINGLE STYLE) WITH APPROXIMATELY 6" OVERLAP, STAPLE THROUGH OVERLAPPED AREA, APPROXIMATELY 12" APART.

TEMPORARY EROSION CONTROL **BLANKET ON SLOPES**


NOT TO SCALE

TEMPORARY EROSION CONTROL BLANKETS NHFG WILDLIFE FRIENDLY REQUIREMENTS

1. THE ELIMINATION OF PLASTIC OR 'BIODEGRADABLE PLASTIC' EROSION CONTROL NETTING IS REQUIRED AS THESE ARE KNOWN SOURCE OF ENTRAPMENT AND MORTALITY TO PROTECTED SNAKES AND TURTLES.

2. SEVERAL 'WILDLIFE FRIENDLY' OPTIONS SUCH AS WOVEN ORGANIC MATERIAL (E.G., COCO MATTING) OR THE USE OF EROSION CONTROL BERM OKAY

3. ACCEPTABLE MATERIALS INCLUDE NORTH AMERICAN GREEN C125BN OR EAST COAST EROSION CONTROL BLANKET ECC-2B BOTH ARE BIODEGRADABLE WITH A COCONUT FIBER MATRIX AND JUTE NETTING.



. DURING THE GROWING SEASON (APRIL 15 - SEPTEMBER 15) USE MATS OR MULCH AND NETTING ON THE BASE OF GRASSED WATERWAYS.

2. DURING THE LATE FALL AND WINTER (SEPTEMBER 15 - APRIL 15) USE HEAVY GRADE MATS ON SIDE SLOPES OF GRASSED

3. INSTALL MATS AND STAPLE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.

4. ALL BLANKET AND MATS SHOULD BE INSPECTED WEEKLY DURING THE CONSTRUCTION PERIOD, AND AFTER ANY RAINFALL EVENT EXCEEDING 1/2 INCH IN A 24-HOUR PERIOD.

5. ANY FAILURE SHOULD BE REPAIRED IMMEDIATELY. IF WASHOUT OF THE SLOPE, DISPLACEMENT OF THE MAT. OR DAMAGE TO THE MAT OCCURS, THE AFFECTED SLOPE SHALL BE REPAIRED AND RESEEDED, AND THE AFFECTED AREA OF MAT SHALL BE RE-INSTALLED OR REPLACED.

SPECIFICATIONS

GRADE AND SHAPE AREA OF INSTALLATION.

7. REMOVE ALL ROCKS, CLODS, TRASH, VEGETATIVE OR OTHER OBSTRUCTIONS SO THAT THE INSTALLED BLANKETS WILL HAVE DIRECT CONTACT WITH THE SOIL.

8. PREPARE SEEDBED BY LOOSENING 2-3 INCHES OF TOPSOIL ABOVE FINAL GRADE.

9. INCORPORATE AMENDMENTS, SUCH AS LIME AND FERTILIZER, INTO SOIL ACCORDING TO SOIL TEST AND THE SEEDING PLAN.

10. SEED AREA BEFORE BLANKET INSTALLATION FOR EROSION CONTROL AND RE-VEGETATION. SEEDING AFTER MAT INSTALLATION IS OFTEN SPECIFIED FOR TURF REINFORCEMENT APPLICATION, WHEN SEEDING PRIOR TO BLANKET INSTALLATION, ALL CHECK SLOTS AND OTHER AREAS DISTURBED DURING INSTALLATION MUST BE RESEEDED.

11. WHERE SOIL FILLING IS SPECIFIED, SEED THE MATTING AND THE ENTIRE DISTURBED AREA AFTER INSTALLATION AND PRIOR TO FILLING THE MAT WITH SOIL.

2. BLANKETS SHALL BE INSTALLED AND ANCHORED PER THE MANUFACTURER'S SPECIFICATIONS.

13. ENSURE COMPLETE CONTACT OF THE PROTECTION MATTING WITH THE SOIL.

4. BLANKETS SHALL BE INSTALLED IN CHANNELS PER THE MANUFACTURER'S SPECIFICATIONS. IF THE MANUFACTURER'S INSTRUCTIONS DIFFER FROM THOSE LISTED BELOW, THE MANUFACTURER'S INSTRUCTIONS SHOULD BE FOLLOWED.

COMPACT THE TRENCH AFTER STAPLING.

16. ROLL CENTER BLANKET IN DIRECTION OF THE INLET END OF THE CHANNEL

17. PLACE BLANKETS END OVER END (SHINGLE STYLE) WITH A 6" OVERLAP. USE A DOUBLE ROW OF STAGGERED STAPLES 4"

18. FULL LENGTH EDGE OF BLANKETS AT TOP OF SIDE SLOPES MUST BE ANCHORED IN 6" DEEP X 6" WIDE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING

19. BLANKETS ON SIDE SLOPES MUST BE OVERLAPPED 4" OVER THE CENTER BLANKET AND STAPLED.

20. IN HIGH FLOW CHANNEL APPLICATIONS, A STAPLE CHECK SLOT IS RECOMMENDED AT 30 TO 40 FOOT INTERVALS. USE A ROW OF STAPLES 4" APART OVER ENTIRE WIDTH OF THE CHANNEL. PLACE A SECOND ROW 4" BELOW THE FIRST ROW IN A

21. THE TERMINAL END OF THE BLANKETS MUST BE ANCHORED IN A 6" DEEP X 6" WIDE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING

> TEMPORARY EROSION CONTROL **BLANKET FOR CHANNELS**

NOT TO SCALE

TEMPORARY & PERMANENT MULCHING

CONSIDERATIONS
1. WITHIN 100 FEET OF STREAMS, WETLANDS AND IN LAKE WATERSHEDS, TEMPORARY MULCH SHOULD BE APPLIED WITHIN 7 DAYS OF EXPOSING SOIL OR PRIOR TO ANY STORM EVENT.

2. AREAS THAT HAVE BEEN TEMPORARILY OR PERMANENTLY SEEDED SHOULD BE MULCHED IMMEDIATELY FOLLOWING SEEDING. 3. AREAS THAT CANNOT BE SEEDED WITHIN THE GROWING SEASON SHOULD BE MULCHED FOR OVER-WINTER PROTECTION. THE AREA SHOULD BE SEEDED AT THE BEGINNING OF THE NEXT GROWING SEASON.

4. MULCH ANCHORING SHOULD BE USED ON SLOPES WITH GRADIENTS GREATER THAN 5% IN LATE FALL (PAST SEPTEMBER 15),

5. PERMANENT MULCH CAN BE USED IN CONJUNCTION WITH TREE, SHRUB, VINE, AND GROUND COVER PLANTINGS.

MAINTENANCE REQUIREMENTS
6. ALL TEMPORARY MULCHES MUST BE INSPECTED PERIODICALLY AND IN PARTICULAR AFTER RAINSTORMS, TO CHECK FOR RILL EROSION OR DISPLACEMENT OF THE MULCH. IF LESS THAN 90% OF THE SOIL SURFACE IS COVERED BY MULCH, ADDITIONAL MULCH SHOULD BE IMMEDIATELY APPLIED. NETS MUST BE INSPECTED AFTER RAIN EVENTS FOR DISLOCATION OR FAILURE. IF WASHOUTS OR BREAKAGES OCCUR, REPAIR ANY DAMAGE TO THE SLOPE AND RE-INSTALL OR REPLACE NETTING AS NECESSARY, INSPECTIONS SHOULD TAKE PLACE UNTIL GRASSES ARE FIRMLY ESTABLISHED (85% SOIL SURFACE UNIFORMLY COVERED WITH HEALTHY STAND OF GRASS)

7. EROSION CONTROL MIX MULCH USED FOR TEMPORARY STABILIZATION SHOULD BE LEFT IN PLACE. VEGETATION ADDS STABILITY AND SHOULD BE PROMOTED.

8. WHERE PERMANENT MULCH IS USED IN CONJUNCTION WITH ORNAMENTAL PLANTINGS. INSPECT PERIODICALLY THROUGHOUT THE YEAR TO DETERMINE IF MULCH IS MAINTAINING COVERAGE OF THE SOIL SURFACE, REPAIR AS NEEDED.

9. PERMANENT MULCHED AREAS SHOULD BE INSPECTED AT LEAST ANNUALLY, AND AFTER EACH LARGE RAINFALL (2.5 INCHES OR MORE IN A 24-HOUR PERIOD). ANY REQUIRED REPAIRS SHOULD BE MADE IMMEDIATELY. WHERE EROSION CONTROL MIX HAS BEEN USED, PLACE ADDITIONAL MIX ON TOP OF THE MULCH TO MAINTAIN THE RECOMMENDED THICKNESS. WHEN THE MULCH IS DECOMPOSED, CLOGGED WITH SEDIMENT, ERODED OR INEFFECTIVE, IT MUST BE REPLACED OR REPAIRED.

10. IF THE MULCH NEEDS TO BE REMOVED, SPREAD IT OUT INTO THE LANDSCAPE.

GENERAL: 11. APPLY MULCH PRIOR TO A STORM EVENT. THIS IS APPLICABLE IN EXTREMELY SENSITIVE AREAS SUCH AS WITHIN 100 FEET OF LAKES, PONDS, RIVERS, STREAMS, AND WETLANDS. IT WILL BE NECESSARY TO CLOSELY MONITOR WEATHER PREDICTIONS TO HAVE ADEQUATE WARNING OF SIGNIFICANT STORMS.

12. MULCHING SHOULD BE COMPLETED WITHIN THE FOLLOWING SPECIFIED TIME PERIODS FROM ORIGINAL SOIL EXPOSURE: WITHIN 100 FEET OF RIVERS AND STREAMS, WETLANDS, AND IN LAKE AND POND WATERSHEDS, THE TIME PERIOD. SHOULD BE NO GREATER THAN 7 DAYS. THIS 7-DAY LIMIT SHOULD BE REDUCED FURTHER DURING WET WEATHER

- IN OTHER AREAS. THE TIME PERIOD CAN RANGE FROM 14 TO 30 DAYS. THE LENGTH OF TIME VARYING WITH SITE CONDITIONS (SOIL ERODIBILITY, SEASON OF YEAR, EXTENT OF DISTURBANCE, PROXIMITY TO SENSITIVE RESOURCES) AND THE POTENTIAL IMPACT OF EROSION ON ADJACENT AREAS. OTHER STATE OR LOCAL RESTRICTIONS MAY ALSO APPLY.

13. THE CHOICE OF MATERIALS FOR MULCHING SHOULD BE BASED ON SITE CONDITIONS, SOILS, SLOPE, FLOW CONDITIONS, AND

14. ORGANIC MULCHES INCLUDING HAY AND STRAW SHOULD BE AIR-DRIED, FREE OF UNDESIRABLE SEEDS AND COARSE

15. APPLICATION RATE SHOULD BE 2 BALES (70-90 POUNDS) PER 1000 SQUARE FEET OR 1.5 TO 2 TONS (90-100 BALES) PER ACRE TO COVER 75 TO 90 % OF THE GROUND SURFACE.

16 HAY OR STRAW MULCH SHOULD BE ANCHORED TO PREVENT DISPLACEMENT BY WIND OR FLOWING WATER, USING ONE OF NETTING: INSTALL JUTE, WOOD FIBER, OR BIODEGRADABLE PLASTIC NETTING OVER HAY OR STRAW TO ANCHOR IT TO

THE SOIL SURFACE. INSTALL NETTING MATERIAL ACCORDING TO MANUFACTURER'S RECOMMENDATION. NETTING SHOULD BE USED JUDICIOUSLY, AS WILDLIFE CAN BECOME ENTANGLED IN THE MATERIALS. - TACKIFIER: APPLY POLYMER OR ORGANIC TACKIFIER TO ANCHOR HAY OOOR STRAW MULCH. APPLICATION RATES VARY BY MANUFACTURER: TYPICALLY 40-60 LBS/ACRE FOR POLYMER MATERIAL. AND 80-120 LBS/ACRE FOR ORGANIC MATERIAL, LIQUID MULCH BINDERS ARE ALSO TYPICALLY APPLIED HEAVIER AT EDGES, IN VALLEYS, AND AT CRESTS

17. WHEN MULCH IS APPLIED TO PROVIDE PROTECTION OVER WINTER (PAST THE GROWING SEASON), IT SHOULD BE APPLIED TO A DEPTH OF FOUR INCHES (150-200 POUNDS OF HAY OR STRAW PER 1000 SQUARE FEET, OR DOUBLE STANDARD APPLICATION RATE). SEEDING CANNOT GENERALLY BE EXPECTED TO GROW UP THROUGH THIS DEPTH OF MULCH AND WILL BE SMOTHERED. IF VEGETATION IS DESIRED, THE MULCH WILL NEED TO BE REMOVED IN THE SPRINGTIME AND THE AREA SEEDED AND MULCHED.

 $\frac{\text{WOOD CHIPS OR BARK:}}{18.\,\text{WOOD CHIPS OR GROUND BARK SHOULD BE APPLIED TO A THICKNESS OF 2 TO 6 INCHES.}}$

19 WOOD CHIPS OR GROUND BARK SHOULD BE APPLIED AT A RATE OF 10 TO 20 TONS PER ACRE OR 460 TO 920 POUNDS PER 1,000 SQUARE FEET.

 20 . EROSION CONTROL MIX CAN BE MANUFACTURED ON OR OFF THE PROJECT SITE. IT MUST CONSIST PRIMARILY OF ORGANIC MATERIAL, SEPARATED AT THE POINT OF GENERATION, AND MAY INCLUDE SHREDDED BARK, STUMP GRINDINGS, COMPOSTED BARK, OR ACCEPTABLE MANUFACTURED PRODUCTS. WOOD AND BARK CHIPS, GROUND CONSTRUCTION DEBRIS OR REPROCESSED WOOD PRODUCTS WILL NOT BE ACCEPTABLE AS THE ORGANIC COMPONENT OF THE MIX.

21 COMPOSITION OF THE EROSION CONTROL MIX SHOULD BE AS FOLLOWS: - EROSION CONTROL MIX SHOULD CONTAIN A WELL-GRADED MIXTURE OF PARTICLE SIZES AND MAY CONTAIN ROCKS LESS HAN 4" IN DIAMETER. EROSION CONTROL MIX MUST BE FREE OF REFUSE. PHYSICAL CONTAMINANTS. AND MATERIA TOXIC TO PLANT GROWTH. THE MIX COMPOSITION SHOULD MEET THE FOLLOWING STANDARDS:

THE ORGANIC MATTER CONTENT SHOULD BE BETWEEN 25 AND 65%, DRY WEIGHT BASIS. PARTICLE SIZE BY WEIGHT SHOULD BE 100% PASSING A 3" SCREEN, 90% TO 100% PASSING A 1-INCH SCREEN, 70% TO 100% PASSING A 0.75-INCH SCREEN, AND A MAXIMUM OF 30% TO 75%, PASSING A 0.25-INCH SCREEN THE ORGANIC PORTION NEEDS TO BE FIBROUS AND ELONGATED.

- THE MIX SHOULD NOT CONTAIN SILTS, CLAYS OR FINE SANDS. SOLUBLE SALTS CONTENT SHOULD BE < 4.0 MMHOS/CM.

- THE PH SHOULD BE BETWEEN 5.0 AND 8.0.

22. THE BARRIER MUST BE PLACED ALONG A RELATIVELY LEVEL CONTOUR. IT MAY BE NECESSARY TO CUT TALL GRASSES OR WOODY VEGETATION TO AVOID CREATING VOIDS AND BRIDGES THAT WOULD ENABLE FINES TO WASH UNDER THE BARRIER

23. THE BARRIER MUST BE A MINIMUM OF 12" HIGH, AS MEASURED ON THE UPHILL SIDE OF THE BARRIER, AND A MINIMUM OF

WINTER CONSTRUCTION NOTES

- ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCT.. 15TH, OR WHICH ARE DISTURBED AFTER OCT. 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.
- 2. ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCT. 15TH, OR WHICH ARE DISTURBED AFTER OCT. 15TH, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS.
- 3. AFTER OCTOBER 15TH, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT ITEM 304.3.

GN-4: VEGETATION STABILIZATION NOTES

ALL VEGETATION STABILIZATION SHALL BE IN ACCORDANCE WITH USDA NRCS "VEGETATING NEW HAMPSHIRE SAND and GRAVEL PITS", IN ADDITION TOO "BEST MANAGEMENT PRACTICES FOR ROUTINE ROADWAY MAINTENANCE ACTIVITIES IN NEW HAMPSHIRE", LATEST EDITIONS.

PARK SEED TYPE 15 SHALL NORMALLY BE USED ON LOAM AREAS. THIS SEED MIXTURE SHALL CONFORM TO TABLE 1 UNLESS AMENDED BY THE PROJECT ENGINEER TO SUIT ACTUAL FIELD CONDITIONS.

	TA	ABLE 1	
KIND OF SEED	MINIMUM	MINIMUM	POUNDS/ACRE
	PURITY (%)	GERMINATION (%)	
CREEPING FESCUE	96	85	40
PERENNIAL RYEGRASS	98	90	50
KENTUCKY BLUEGRASS	97	85	25
REDTOP	95	80	5
		TC	TAL 120

SLOPE SEED TYPE 44 SHALL NORMALLY BE USED FOR ALL SLOPE WORK, and SHALL CONFORM TO TABLE 2 UNLESS AMENDED BY THE DESIGN ENGINEER TO SUIT ACTUAL

	TA	BLE <u>2</u>	
KIND OF SEED	MINIMUM	MINIMUM	POUNDS/ACRE
	PURITY (%)	GERMINATION (%)	
CREEPING RED FESCUE	96	85	35
PERENNIAL RYEGRASS	98	90	30
REDTOP	95	80	5
ALSIKE CLOVER	97	90	5
BIRDSFOOT TREFOIL	98	80	5
		TO	TAI 80

SEEDING SEASON:

A. ALL AREAS TO BE SEEDED SHALL BE A REASONABLY FIRM, BUT FRIABLE.

- SURFACE and SEEPAGE WATER SHOULD BE DRAINED OR DIVERTED FROM THE SITE TO PREVENT DROWNING OR WINTER KILLING.
- C. THE SEEDBED SHOULD BE LEFT IN A REASONABLY FIRM and SMOOTH CONDITION, FOLLOWING SEEDING OPERATIONS.
- ALL AREAS TO BE SEEDED SHALL MEET THE SPECIFIED GRADES, AS SPECIFIED ON THE APPROVED PLAN.
- ALL VEGETATION SHALL BE INSPECTED ANNUALLY FOR UNHEALTHY or DEAD AREAS. ANY and ALL SUCH AREAS ARE TO BE REPAIRED or REPLACED IN KIND.

2. ESTABLISHING A STAND

- A. LIME AND FERTILIZER SHOULD BE APPLIED PRIOR TO OR AT THE TIME OF SEEDING AND INCORPORATED INTO THE SOIL. KINDS AND AMOUNTS OF LIME AND FERTILIZER SHOULD BE BASED ON EVALUATION OF SOIL TESTS. WHEN A SOIL TEST IS NOT AVAILABLE, THE
 - FOLLOWING MINIMUM AMOUNTS SHOULD BE APPLIED: AGRICULTURAL LIMESTONE: 2 TONS PER ACRE OR 0.09 LBS. PER SQ. FT.
 - NITROGEN (N): 50 LBS. PER ACRE OR 1.1 LBS. PER 1000 SQ. FT.
 - PHOSPHATE (P₂O₅): 100 LBS. PER ACRE OR 2.2 LBS. PER 1000 SQ. FT. - POTASH (K₂O); 100 LBS, PER ACRE OR 2,2 LBS, PER 1000 SQ, FT.
 - (NOTE: THIS IS THE EQUIVALENT OF 500 LBS. PER ACRE OF 10-20-20 FERTILIZER OR 1,000 LBS. PER ACRE OF 5-10-10)

SEED SHOULD BE SPREAD UNIFORMLY BY THE METHOD MOST APPROPRIATE FOR THE SITE. METHODS INCLUDE BROADCASTING, DRILLING, AND HYDROSEEDING. WHERE BROADCASTING IS USED, COVER SEED WITH 0.25 INCH O SOIL OR LESS, BY CULTIPACKING OR RAKING.

HAY, STRAW, OR OTHER MULCH, WHEN NEEDED, SHOULD BE APPLIED IMMEDIATELY AFTER

MULCH WILL BE HELD IN PLACE USING TECHNIQUES FROM THE "BEST MANAGEMENT PRACTICE FOR MULCHING", AS SHOWN IN, "STORMWATER MANAGEMENT AND SEDIMENTATION CONTROL HANDBOOK FOR URBAN AND DEVELOPING AREAS IN NEW HAMPSHIRE".

4. MAINTENANCE TO ESTABLISH A STAND

- PLANTED AREAS SHOULD BE PROTECTED FROM DAMAGE BY FIRE, GRAZING, TRAFFIC, AND DENSE WEED GROWTH.
- FERTILIZATION WILL BE PERFORMED ANNUALLY IN ACCORDANCE WITH NOTE 2A..
- IN WATERWAYS, CHANNELS, OR SWALES WHERE UNIFORM FLOW CONDITIONS ARE ANTICIPATED, OCCASIONAL MOWING or TRIMMING WILL BE PERFORMED ANNUALLY TO CONTROL GROWTH.
- ALL VEGETATION SHOULD BE INSPECTED REGULARLY and AFTER EVERY MAJOR RAIN EVENT (> 5"/24 hr). DAMAGED AREAS SHOULD BE REPAIRED AND RE-VEGETATED IMMEDIATELY.



Developer: **DBU CONSTRUCTION** PO Box 984 Epsom, NH 03234

EROSION CONTROL DETAIL COMMERCIAL SITE PLAN TAX PARCEL 4 LOT 151 **DOVER ROAD** CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

	1 (= 1) 0 0 1	GRATE H20 LOADING	
DATE	DESCRIPTION	DWN BY	CK BY
	52001W 11011	5 5.	OIX DI

REVISIONS

Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688

SCALE: 1" = 50"DATE: JANUARY 14, 2019 DR. BY: JR CK. BY: JR JOB NO. _____ SHEET NO. 23 OF 23

Registry	Book	&	Page		

CHICHESTER PLANNING BOARD

SITE PLAN REVIEW APPLICATION

Owner of Record:	Mal-Mar, LLC	Date Received:	
4 Map Number:	: Mal-Mar, LLC 150C & Lot Number:F	k 150E ee Paid: Check I	Number:
	over Road, Chicheste		
Daytime Phone N	fumber: 603-765-0013	Evening Phone Number:	
Prepared by: Ro	okeh Consulting, LLC	***************************************	
Address: PO B	OX 204, EPSOM NH 0	3234	
Daytime Phone N	fumber: 603-387-8688	_Evening Phone Number:	
1. Road Location:	9 Dover Road		
2. Property Locate	ed in a CI / MF zor	ne.	
3. Land is in open	space (current use):	YES; X NO	00.000
4. Area of entire t	ract: 10.6671 (acres).	Portion to be utilized:	93,000 sf (acres or square
5. Describe planne	ed use:		
	on of the site is prop storage area for the e		
Chichester and the making this appl	rees that he/she is familiar whe Laws of the State of New lication, has complied with the	Hampshire governing site	
Property Owner	or Applicant	Date	

Chichester Planning Board Site Plan Review Checklist

In cases where not all items are applicable, draw a line through the items.

APPLICABLE	INCLUDED			
(Y/N)	(Y/N)	INITIALS		
Y			1.	Three copies of the completed application and checklist
Y			2.	Site plan: 22" by 34" sheet size maximum,
			۷.	scale not less than 1" =100', match lines
				where needed, boundaries, water courses &
				bodies of water, trees and other vegetation,
				topography at 2' intervals to USGS datum,
				existing and proposed contours and finished
				grade elevations and other pertinent features,
				date, title, graphic scale, north arrow,
				location map, name & address of
				developer/applicant, designer/engineer,
				owner of record. On mylar sufficient to
Y				record.
			3.	List of names and addresses of abutters and
				owners of land within 200' of any property
Y				line. (YOU MAY NOT ABUT YOURSELF)
<u> </u>			4.	The appropriate fee
			5.	Plan of all buildings depicting their type,
Y				size, and location (setbacks)
<u> </u>			6.	An elevation view or photo of all buildings
<u> </u>			7. 8.	Layout of off-street parking and loading
<u></u>			٥.	Ingress-egress of site and depiction of streets both within and adjacent to site
Y			9.	Solid waste disposal facilities
Υ			10.	Location; size, and design of signs and
				advertising or instructional devices
Y			11.	Location, type, direction, and illuminated
-				area of outside lighting
Υ			12.	Other required exhibits or data, any permits
				specific to site.
			13.	Permanent first floor elevation of proposed
Y				buildings
			14.	Existing water supply and sewage disposal
				facilities on the site and within 200' of the
				site, proposed water and sewage facilities,
				and provisions for expansion of water and sewage facilities
Y			15.	Location, elevation, and layout of surface
			10,	drainage facilities
Y			16.	Existing and proposed landscaping and open
				space areas and treatment
Y			17.	Gas, electric, telephone, CATV utility lines

Y	1	8. Boundry survey shown
Υ		9. Description or depiction of proposed
		grading, filling, or other site preparation
<u> </u>	2	O. Existing and proposed buffers
Y	2	1. Existing and proposed screening
Υ	2	2. Sidewalks, access, loading & parking
Υ	2:	3. Erosion and sedimentation control plan
Y	24	4. Flood plain areas
Y	2:	5. Town Engineer authorization
Y		6. Wetlands Setbacks.

\$ 7.



The State of New Hampshire

Department of Environmental Services



Robert R. Scott, Commissioner

March 16, 2020

Mr. Mark Blanchard Mal-Mar, LLC 9 Dover Road Chichester, NH 03258

Re: Site Plan for Bobcat of NH Permit: AoT-1765

9 Dover Road – Chichester, NH Tax Map 4 Lots 150B, 150C & 150E

Dear Applicant:

Based upon the plans and application, approved on March 16, 2020, we are hereby issuing RSA 485-A:17 Alteration of Terrain Permit AoT-1765. The permit is subject to the following conditions:

PROJECT SPECIFIC CONDITIONS:

- 1. The approved plans, dated October 2, 2019, latest revision dated March 16, 2020, and supporting documentation in the permit file are a part of this approval.
- 2. This permit expires on March 16, 2025. No earth moving activities shall occur on the project after this expiration date unless the permit has been extended by the Department. If requesting an extension, the request must be received by the department <u>before the permit expires</u>. The Amendment Request form is available at: http://des.nh.gov/organization/divisions/water/aot/categories/forms.htm
- 3. In accordance with Env-Wq 1503.21 (c)(1), a written notice signed by the permit holder and a qualified engineer shall be submitted to DES stating that the project was completed in accordance with the approved plans and specifications. If deviations were made, the permit holder shall review the requirements in Env-Wq 1503.21(c)(2).
- 4. Plans show that shared stormwater best management practices (BMPs) are located within drainage easements on two lots. In accordance with Env-Wq 1504.07(d), copies of recorded easements must be submitted to DES within 7 days of recording with the Registry of Deeds. Alternatively, if the lots are merged, submit a recorded deed and recorded copy of the lot consolidation plan.
- 5. The permittee shall employ the services of an Environmental Monitor (EM) for the purposes of providing independent professional environmental inspections of the project. The permittee shall receive prior approval of the EM by the Department. The EM shall inspect the project at a minimum frequency of once per week and following rainfall events of 0.5-inch or greater in a 24-hour period. The inspections shall be for the purposes of determining compliance with the permit. The Monitor shall submit a written report, stamped by a qualified engineer or a Certified Professional in Erosion and Sediment Control to the Department within 24 hours of the inspections. The reports shall describe, at a minimum, whether the project is being constructed in accordance with the approved sequence, shall identify any deviation from the conditions of this permit and the approved plans, and identify any other noted deficiencies. Reports should be submitted to <a href="microater.com/microa

Alteration of Terrain Permit, AoT-1765 Site Plan for Bobcat of NH Tax Map 4 Lots 150B, 150C & 150E – Chichester, NH Page 2 of 2

GENERAL CONDITIONS:

- 1. Activities shall not cause or contribute to any violations of the surface water quality standards established in Administrative Rule Env-Wq 1700.
- 2. You must submit revised plans for permit amendment prior to any changes in construction details or sequences. You must notify the Department in writing within ten days of a change in ownership.
- 3. You must notify the Department in writing prior to the start of construction and upon completion of construction. Forms can be submitted electronically at: https://forms.nh.gov/onlineforms/. Paper forms are available at that same web page.
- 4. All stormwater practices shall be inspected and maintained in accordance with Env-Wq 1507.07 and the project Inspection and Maintenance (I&M) Manual. All record keeping required by the I&M Manual shall be maintained by the identified responsible party, and be made available to the department upon request. Photographs of the site and BMPs must accompany the I&M submittals.
- 5. This permit does not relieve the applicant from the obligation to obtain other local, state or federal permits that may be required (e.g., from US EPA, US Army Corps of Engineers, etc.). Projects disturbing over 1 acre may require a federal stormwater permit from EPA. Information regarding this permitting process can be obtained at: http://des.nh.gov/organization/divisions/water/stormwater/construction.htm.
- 6. If applicable, no activity shall occur in wetland areas until a Wetlands Permit is obtained from the Department. Issuance of this permit does not obligate the Department to approve a Wetlands Permit for this project.
- 7. This project has been screened for potential impact to known occurrences of protected species and exemplary natural communities in the immediate area. Since many areas have never been surveyed, or have not been surveyed in detail, unidentified sensitive species or communities may be present. This permit does not absolve the permittee from due diligence in regard to state, local or federal laws regarding such communities or species.

Sincerely,


Michael Schlosser, PE


mil Selle


Alteration of Terrain Bureau


cc: Chichester Planning Board


Jon Rokeh, Rokeh Consulting, LLC (via email)











- THE EXIT SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. WHEN THE CONTROL PAD BECOMES INEFFECTIVE, THE STONE SHALL BE REMOVED ALONG WITH THE COLLECTED SOIL MATERIAL, REGRADED ON SITE, AND STABILIZED. THE ENTRANCE SHALL THEN BE
- 2. THE CONTRACTOR SHALL SWEEP THE PAVEMENT AT EXITS WHENEVER SOIL MATERIALS ARE TRACKED ONTO THE ADJACENT PAVEMENT OR TRAVELED WAY.
- 3. WHEN WHEEL WASHING IS REQUIRED, IT SHALL BE CONDUCTED ON AN AREA STABILIZED WITH AGGREGATE, WHICH DRAINS INTO AN APPROVED SEDIMENT—TRAPPING DEVICE. ALL SEDIMENT SHALL BE PREVENTED FROM ENTERING STORM DRAINS, DITCHES, OR WATERWAYS.

- CONSTRUCTION SPECIFICATIONS
 4. ONLY CONSTRUCTION TRAFFIC LEAVING THE SITE IS REQUIRED TO USE THE TEMPORARY STABILIZED EXIT. CONSIDER PROVIDING A SEPARATE, UNPROTECTED, ENTRANCE FOR TRAFFIC ENTERING THE SITE. THIS WILL INCREASE THE LONGEVITY OF THE STABILIZED EXIT BY ELIMINATING HEAVY LOADS ENTERING THE SITE AND REDUCING THE TOTAL TRAFFIC OVER THE DEVICE.
- 5. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOP DRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND, AND REPAIR AND/OR MAINTENANCE OF ANY MEASURES USED TO TRAP
- 6. STONE FOR A TEMPORARY CONSTRUCTION EXIT SHALL BE 3 INCH STONE, RECLAIMED STONE, OR RECYCLED CONCRETE EQUIVALENT.
- 7. THE MINIMUM LENGTH OF THE PAD SHALL BE 75 FEET, EXCEPT THAT THE MINIMUM LENGTH MAY BE REDUCED TO 50 FEET IF A 3-INCH TO 6-INCH HIGH BERM IS INSTALLED AT THE ENTRANCE OF THE
- 8. THE THICKNESS OF THE STONE FOR THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 6 INCHES.
- 9. THE WIDTH OF THE ENTRANCE SHALL NOT BE LESS THAN THE FULL WIDTH OF THE EXIT OR 10 FEET, WHICH EVER IS GREATER.
- 10. GEOTEXTILE FILTER CLOTH SHALL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING THE STONE.
- 11. ALL SURFACE WATER THAT IS FLOWING TO OR DIVERTED TOWARD THE CONSTRUCTION EXIT SHALL BE PIPED BENEATH THE ENTRANCE. IF PIPING IS IMPRACTICAL, A BERM WITH 5:1 SLOPES THAT CAN BE CROSSED BY VEHICLES MAY BE SUBSTITUTED FOR THE PIPE.

TEMPORARY CONSTRUCTION EXIT NOT TO SCALE

CONSTRUCTION SEQUENCES:

NOTE: - ALL EROSION CONTROLS TO BE INSPECTED WEEKLY AND AFTER EVERY .5" OF RAINFALL. AN ENVIRONMENTAL MONITOR WILL BE REQUIRED DUE TO THE AREA OF DISTRUBANCE BEING GREATER THAN 5 ACRES. THE MONITOR SHALL ADHERE TO ALL REQUIREMENTS OF ENV-WQ 1505.03(D)

- PRIOR TO CONSTRUCTION INSTALL FABRIC SILTATION FENCING AS SHOWN ON PLAN
- CONSTRUCT TEMPORARY STABILIZED ENTRANCE, AND INSTALL OTHER APPROPRIATE SEDIMENT AND EROSION CONTROL. 2. CUT AND CLEAR ALL VEGETATION AND STUMPS FROM CUT SLOPES, PONDS, AND SWALE AREAS.
- 3. COMPLETE TEMPORARAY SEDIMENT BASINS AT POND LOCATIONS. CONSTRUCT BERMS AND SWALES TO DIRECT STORMWATER TO BASINS. SEDIMENT BASINS LOCATED WITHIN PROPOSED INFILTATION BASIN AREAS ARE TO BE CONSTRUCTED A MINIMUM OF 1' ABOVE THE FINAL BASIN FLOOR ELEVATION.
- 4. AN AREA IS CONSIDERED STABLE IF: A.) BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED;
- B.) A MINIMUM OF 85% VEGETATED GROWTH HAS BEEN ESTABLISHED; A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE. OR RIP-RAP HAS BEEN INSTALLED: OR
- D.) EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED.
- 5. CUT AND CLEAR ALL VEGETATION AND STUMPS FROM AREAS TO BE DISTURBED FOR THE CONSTRUCTION OF THE
- 6. REMOVE TOPSOIL AND OTHER ORGANIC MATERIALS FROM AREAS TO BE DISTURBED. ALL SUCH TOPSOIL REMOVED SHALL BE STOCKPILED FOR LATER USE. ALL STOCKPILES SHALL BE SEEDED AND MULCHED TO PREVENT LOSS DUE TO EROSION. AND ENCIRCLED WITH FABRIC SILT FENCE. WHEN CONSTRUCTION ACTIVITIES ARE TEMPORARILY CEASED FOR MORE THAN 21 DAYS, PERMANENTLY CEASED, OR SHUT DOWN FOR WINTER, THE CONTRACTOR SHALL LEAVE NO SLOPES STEEPER THAN 3:1 AND SHALL IMPLEMENT TEMPORARY LOAMING, SEEDING AND MULCHING. WHERE CONSTRUCTION ACTIVITIES HAVE BEEN SUSPENDED OUTSIDE THE GROWING SEASON ALL EXPOSED SOIL SHALL BE STABILIZED BY MULCHING, AND ALL SLOPES GREATER THAN 3:1 SHALL BE STABILIZED WITH NETTING & PINNING.
- 7. CONSTRUCT, CUT, AND FILL SLOPES. ALL CUT AND FILL SLOPES TO BE STABILIZED IMMEDIATELY AFTER CONSTRUCTION. ALL SLOPES GREATER THAN 3:1 TO BE STABILIZED WITH JUTE MATTING. ALL CUT AND FILL SLOPES SHALL BE SEEDED AND LOAMED WITHIN 72 HOURS OF ACHIEVING FINISH GRADE.
- 8. CONSTRUCT STORM DRAINAGE, AND OTHER UNDERGROUND UTILITIES. ALL SWALES TO BE PROTECTED WITH TEMPORARY EROSION CONTROL MEASURES SHOWN. ALL CATCH BASIN OPENINGS TO BE PROTECTED WITH BLOCK AND GRAVEL INLET SEDIMENT FILTERS AS SHOWN. SEDIMENT TRAPS AND/OR BASINS SHOULD BE USED UNTIL BASINS/PONDS ARE STABILIZED
- 9. BEGIN TOP SOILING, SEEDING AND Mulching IMMEDIATELY AFTER COMPLETION OF EMBANKMENTS. TEMPORARY EROSION CONTROL / DIVERSION CHANNELS SHALL BE IMPLEMENTED WHERE REQUIRED TO PREVENT EROSION OF EMBANKMENTS. ANY EROSION OCCURRING SHALL BE REPAIRED IMMEDIATELY UPON DISCOVERY.
- 10. FINISH GRADING & PAVING. ALL ROADWAYS AND PARKING LOTS SHALL BE STABILIZED WITHIN 72 HOURS OF ACHIEVING FINISH GRADES.
- 11. ALL PAVED AREAS TO BE COMPLETED BY OCTOBER 15. ALL LANDSCAPED AREAS TO BE STABILIZED BY OCTOBER 15th, WITH HAY MULCH AND SEED.
- 12. COMPLETE PERMANENT SEEDING AND MULCHING OF ALL DISTURBED AREAS, ALL TEMPORARY EROSION CONTROL
- MEASURES TO REMAIN IN PLACE UNTIL A FULL VEGETATIVE COVER HAS BEEN ESTABLISHED ON ALL DISTURBED AREAS. 13. SILT FENCES AND HAY BALE BARRIERS TO BE REMOVED ONCE THE SITE HAS STABILIZED

- 1. TEMPORARY SEEDING SHALL BE INSPECTED WEEKLY AND AFTER ANY RAINFALL EXCEEDING 1/2 INCH IN 24 HOURS ON ACTIVE CONSTRUCTION SITES. TEMPORARY SEEDING SHALL ALSO BE INSPECTED JUST PRIOR TO SEPTEMBER 15, TO ASCERTAIN WHETHER ADDITIONAL SEEDING IS REQUIRED TO PROVIDE STABILIZATION OVER
- 2. BASED ON INSPECTION, AREAS SHALL BE RESEEDED TO ACHIEVE FULL STABILIZATION OF EXPOSED SOILS, IF IT IS TOO LATE IN THE PLANTING SEASON TO APPLY ADDITIONAL SEED, THEN OTHER TEMPORARY STABILIZATION MEASURES SHALL BE IMPLEMENTED
- 3. AT A MINIMUM, 85% OF THE SOIL SURFACE SHALL BE COVERED BY VEGETATION.
- 4. IF ANY EVIDENCE OF EROSION OR SEDIMENTATION IS APPARENT, REPAIRS SHALL BE MADE AND AREAS SHALL BE RESEEDED, WITH OTHER TEMPORARY MEASURES (E.G., MULCH) USED TO PROVIDE EROSION PROTECTION DURING THE PERIOD OF VEGETATION ESTABLISHMENT.

- 5. INSTALL NEEDED EROSION AND SEDIMENT CONTROL MEASURES SUCH AS SILTATION BARRIERS, DIVERSIONS, AND SEDIMENT TRAPS.
- 6. GRADE AS NEEDED FOR THE ACCESS OF EQUIPMENT FOR SEEDBED PREPARATION, SEEDING, MULCH APPLICATION, AND MULCH ANCHORING.
- 7. RUNOFF SHALL BE DIVERTED FROM THE SEEDED AREA.
- 8. ON SLOPES 4:1 OR STEEPER, THE FINAL PREPARATION SHALL INCLUDE CREATING HORIZONTAL GROOVES PERPENDICULAR TO THE DIRECTION OF THE SLOPE TO CATCH SEED AND REDUCE RUNOFF.

- 9. STONES AND TRASH SHALL BE REMOVED SO AS NOT TO INTERFERE WITH THE SEEDING AREA.
- 10. WHERE THE SOIL HAS BEEN COMPACTED BY CONSTRUCTION OPERATIONS, LOOSEN SOIL TO A DEPTH OF 2 INCHES BEFORE APPLYING FERTILIZER, LIME AND SEED.
- 11. IF APPLICABLE, FERTILIZER AND ORGANIC SOIL AMENDMENTS SHALL BE APPLIED DURING THE GROWING
- SEASON. - APPLY LIMESTONE AND FERTILIZER ACCORDING TO SOIL TEST RECOMMENDATIONS. IF SOIL TESTING IS NOT FEASIBLE ON SMALL OR VARIABLE SITES, OR WHERE TIMING IS CRITICAL, FERTILIZER MAY BE APPLIED AT THE RATE OF 1000 POUNDS PER ACRE OR 13.8 POUNDS PER 1,000 SQUARE FEET OF LOW PHOSPHATE FERTILIZER1 (N-P205-K20) OR EQUIVALENT. APPLY LIMESTONE (EQUIVALENT TO 50 PERCENT CALCIUM PLUS MAGNESIUM OXIDE) AT A RATE OF 3 TONS PER ACRE (138 LB. PER 1,000 SQUARE FEET).
- FERTILIZER SHALL BE RESTRICTED TO A LOW PHOSPHATE, SLOW RELEASE2 NITROGEN FERTILIZER WHEN APPLIED TO AREAS BETWEEN 25 FEET AND 250 FEET FROM A SURFACE WATER BODY. NO FERTILIZER EXCEPT LIMESTONE SHALL BE APPLIED WITHIN 25 FEET OF A SURFACE WATER BODY. THESE LIMITATIONS ARE REQUIREMENTS FOR ANY WATER BODY PROTECTED BY THE COMPREHENSIVE SHORELAND PROTECTION ACT.

12. SELECT SEED FROM RECOMMENDATIONS IN TABLE 4-1.

- 13. APPLY SEED UNIFORMLY BY HAND, CYCLONE SEEDER, DRILL, CULTIPACKER TYPE SEEDER OR HYDROSEEDER (SLURRY INCLUDING SEED AND FERTILIZER). NORMAL SEEDING DEPTH IS FROM 1/4 TO 1/2 INCH. HYDROSEEDING THAT INCLUDES MULCH MAY BE LEFT ON SOIL SURFACE. SEEDING RATES MUST BE INCREASED 10 % WHEN HYDROSEEDING
- 14. TEMPORARY SEEDING SHALL TYPICALLY OCCUR PRIOR TO SEPTEMBER 15TH.
- 15. AREAS SEEDED BETWEEN MAY 15TH AND AUGUST 15TH SHALL BE COVERED WITH HAY OR STRAW MULCH, ACCORDING TO THE "TEMPORARY AND PERMANENT MULCHING" PRACTICE.
- 16. VEGETATED GROWTH COVERING AT LEAST 85% OF THE DISTURBED AREA SHALL BE ACHIEVED PRIOR TO OCTOBER 15TH. IF THIS CONDITION IS NOT ACHIEVED, IMPLEMENT OTHER TEMPORARY STABILIZATION MEASURES FOR OVERWINTER PROTECTION.

TABLE 4-1. SEEDING RECOMMENDATIONS FOR TEMPORARY VEGETATION PER ACRE BUSHELS PER 1,000 FT2 REMARKS WINTER RYE 2 BU. OR 112 LBS. BEST FOR FALL SEEDING. SEED FROM AUGUST 15 TO SEPTEMBER 15 FOR BEST COVER. SEED TO A DEPTH 2.5 BU. OR 80 LBS. SPRING SEEDINGS. SEED NO LATER THAN MAY 15 FOR SUMMER PROTECTION. SEED TO A DEPTH OF 1 ANNUAL RYEGRASS 40 LBS. GROWS QUICKLY, BUT IS OF SHORT DURATION. USE WHERE APPEARANCES ARE IMPORTANT. SEED EARLY SPRING AND/OR BETWEEN AUGUST 15 AND SÉPTEMBER 15. COVER THE SEED WITH NO MORE THAN 0.25

GOOD COVER WHICH IS LONGER LASTING THAN ANNUAL RYEGRASS. SEED BETWEEN APRIL 1 AND TEMPORARY VEGETATION IN 1 AND/OR BETWEEN AUGUST T NUNE 1 AND/OR BETWEEN AUGUST 15


INCH OF SOIL.

SEEDING THROUGHOUT THE <u>GROWING SEASON. SEED TO A DEPTH</u> 14. REMOVE ACCUMULATIONS OF SEDIMENT FROM DRAINAGE STRUCTURES A MIRTRO MOVING TERONIO. 50 INICHCLEANED OUT LOAMED & MATTED AS NECESSARY UPON COMPLETION OF PROJECT

15. THE MAXIMUM AMOUNT OF AREA ALLOWED TO BE DISTURBED & UNSTABILIZED AT ONE TIME IS 1.5 ACRES. ALL AREAS SHALL BE STABILIZED WITHIN 45 DAYS FROM INITIAL DISTURBANCE.

PERENNIAL RYEGRASS

- A.) DURING WINTER CONDITIONS, THE MAXIMUM ALLOWABLE DISTURBED AREA SHALL BE 0.5 ACRES. B.) ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MAXIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15th, OR WHICH ARE DISTURBED AFTER OCTOBER 15th, SHALL BE STABILIZED BY SEEDING AND INSTALLING FROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1. AND SEFDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING, ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.
- C.) ALL DITCHES AND SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCTOBER 15th, OR WHICH ARE DISTURBED AFTER OCTOBER 15th, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS. D.) AFTER OCTOBER 15th, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER
- SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER N.H.D.O.T. ITEM 304.3.
- 17. AN AREA SHALL BE CONSIDERED STABLE IF ONE OF THE FOLLOWING HAS OCCURRED: A.) BASE COURSE GRAVELS HAVE BEEN INSTALLED IN AREAS TO BE PAVED; B.) A MINIMUM OF 85% VEGETATIVE GROWTH HAS BEEN ESTABLISHED;
 - C.) A MINIMUM OF 3" OF NON-EROSIVE MATERIAL SUCH AS STONE OR RIPRAP HAS BEEN INSTALLED; OR D.) EROSION CONTROL BLANKETS HAVE BEEN PROPERLY INSTALLED
- 18. BASINS AND SWALES SHALL BE INSTALLED EARLY IN THE CONSTRUCTION SEQUENCE AND PRIOR TO
- ANY ROUGH GRADING OF THE SITE. 19. ALL DITCHES, SWALES AND BASINS SHALL BE STABILIZED PRIOR TO DIRECTING RUNOFF TO THEM.



CONSIDERATIONS

1. THIS PRACTICE IS INTENDED FOR USE IN AREAS OF CONCENTRATED FLOW, BUT MUST NOT BE USED IN STREAM CHANNELS (WHETHER PERENNIAL OR INTERMITTENT).

- 2. THE CHECK DAM MAY BE LEFT IN PLACE PERMANENTLY TO AVOID UNNECESSARY DISTURBANCE OF THE SOIL ON REMOVAL, BUT ONLY IF THE PROJECT DESIGN HAS ACCOUNTED FOR THEIR HYDRAULIC PERFORMANCE AND CONSTRUCTION PLANS CALL FOR THEM TO BE RETAINED.
- 3. IF IT IS NECESSARY TO REMOVE A STONE CHECK DAM FROM A GRASSLINED CHANNEL THAT WILL BE MOWED, CARE SHALL BE TAKEN TO ENSURE THAT ALL STONES ARE REMOVED. THIS INCLUDES STONE THAT HAS

INLET

- 4. CHECK DAMS SHALL BE INSPECTED AFTER EACH RAINFALL AND AT LEAST DAILY DURING PROLONGED RAINFALL AND NECESSARY REPAIRS SHALL BE MADE IMMEDIATELY.
- 5. INSPECTIONS SHALL VERIFY THAT THE CENTER OF THE DAM IS LOWER THAN THE EDGES. 6. EROSION CAUSED BY HIGH FLOWS AROUND THE EDGES OF THE DAM MUST BE CORRECTED IMMEDIATELY.
- 7. IF EVIDENCE OF SILTATION IN THE WATER IS APPARENT DOWNSTREAM FROM THE CHECK DAM, THE CHECK DAM SHALL BE INSPECTED AND ADJUSTED IMMEDIATELY.
- 8. CHECK DAMS SHALL BE CHECKED FOR SEDIMENT ACCUMULATION AFTER EACH SIGNIFICANT RAINFALL. SEDIMENT SHALL BE REMOVED WHEN IT REACHES ONE HALF OF THE ORIGINAL HEIGHT OR BEFORE.

9. CHECK DAMS SHALL BE INSTALLED BEFORE RUNOFF IS DIRECTED TO THE SWALE OR DRAINAGE DITCH.

- 10. THE MAXIMUM CONTRIBUTING DRAINAGE AREA TO THE DAM SHALL BE LESS THAN ONE ACRE.
- 11. THE MAXIMUM HEIGHT OF THE DAM SHALL BE 2 FEET.
- 12. THE CENTER OF THE DAM SHALL BE AT LEAST 6 INCHES LOWER THAN THE OUTER EDGES.
- 13. THE MAXIMUM SPACING BETWEEN THE DAMS SHALL BE SUCH THAT THE TOE OF THE UPSTREAM DAM IS AT THE SAME ELEVATION AS THE OVERFLOW ELEVATION OF THE DOWNSTREAM DAM.
- 14. STONE CHECK DAMS SHALL BE CONSTRUCTED OF A WELL-GRADED ANGULAR 2-INCH TO 3-INCH STONE. 3/4-INCH STONE ON THE UPGRADIENT FACE IS RECOMMENDED FOR BETTER FILTERING.
- 15. IF PROVIDED BY DESIGN AND CONSTRUCTION PLANS, LEAVE THE DAM IN PLACE PERMANENTLY.


THE CHECK DAM MUST BE SEEDED AND MULCHED IMMEDIATELY AFTER REMOVAL.

18. TEMPORARY STRUCTURES SHALL BE REMOVED ONCE THE SWALE OR DITCH HAS BEEN STABILIZED: - IN TEMPORARY DITCHES AND SWALES, CHECK DAMS SHALL BE REMOVED AND THE DITCH FILLED IN WHEN IT IS NO LONGER NEEDED. - IN PERMANENT STRUCTURES, CHECK DAMS SHALL BE REMOVED WHEN A PERMANENT LINING HAS BEEN ESTABLISHED. IF THE PERMANENT LINING IS VEGETATION, THEN THE CHECK DAM SHALL BE RETAINED UNTIL THE GRASS HAS MATURED TO PROTECT THE DITCH OR SWALE. THE AREA BENEATH

TEMPORARY STONE CHECK DAMS

NOT TO SCALE

DIMENSION AS SHOWN ON PLAN





T BARRIERS SHALL BE INSPECTED BEFORE AND AFTER EACH RAIN EVENT AND REPAIRED AS NEEDED.

2. SEDIMENT SHALL BE REMOVED AND THE STORM DRAIN SEDIMENT BARRIER RESTORED TO ITS ORIGINAL DIMENSIONS WHEN THE SEDIMENT HAS ACCUMULATED TO 1/2 THE DESIGN DEPTH OF THE BARRIER. REMOVED SEDIMENT SHALL BE DEPOSITED IN A SUITABLE AREA AND IN SUCH A MANNER THAT IT WILL NOT ERODE.

- 3. THE BARRIERS SHALL BE REMOVED AND THE AREA STABILIZED WHEN THE CONTRIBUTING DRAINAGE AREA HAS BEEN PROPERLY STABILIZED.
- 4. ALL CATCH BASINS AND STORM DRAIN INLETS MUST BE CLEANED AT THE END OF CONSTRUCTION AND AFTER THE SITE HAS BEEN FULLY STABILIZED.

. THE MAXIMUM CONTRIBUTING DRAINAGE AREA TO THE TRAP SHALL BE LESS THAN ONE ACRE.


- 6. THE INLET PROTECTION DEVICE SHALL BE CONSTRUCTED IN A MANNER THAT WILL FACILITATE CLEAN-OUT AND DISPOSAL OF TRAPPED SEDIMENTS AND MINIMIZE INTERFERENCE WITH CONSTRUCTION ACTIVITIES.
- 7. ANY RESULTANT PONDING OF STORMWATER MUST NOT CAUSE EXCESSIVE INCONVENIENCE OR DAMAGE TO ADJACENT AREAS OR STRUCTURES.
- 8. THE BLOCKS SHALL BE PLACED LENGTHWISE IN A SINGLE ROW AROUND THE PERIMETER OF THE INLET.
- 9. THE BLOCK ENDS SHALL ABUT ONE ANOTHER.
- 10. THE HEIGHT OF THE BARRIER CAN BE VARIED, DEPENDING ON DESIGN NEEDS, BY STACKING COMBINATIONS OF 4-INCH, 8-INCH AND 12-INCH WIDE BLOCKS. THE BARRIER OF BLOCKS AND GRAVEL FILTER SHALL BE A MINIMUM OF 12 INCHES HIGH AND NO MORE THAN 24 INCHES HIGH.
- 11. A HARDWARE CLOTH OR WIRE MESH SHALL BE PLACED OVER THE OPENINGS OF THE CONCRETE BLOCKS AND EXTEND AT LEAST 12 INCHES AROUND THE OPENING TO PREVENT AGGREGATE FROM BEING TRANSPORTED THROUGH THE OPENINGS IN THE BLOCKS. HARDWARE CLOTH OR COMPARABLE WIRE MESH WITH 1/2-INCH OPENINGS SHALL BE USED.
- 12. THE GRAVEL FILTER SHALL BE CLEAN COARSE AGGREGATE.
- 13. THE GRAVEL SHALL BE PLACED AGAINST THE WIRE AND ALONG THE OUTSIDE EDGES OF THE BLOCKS TO THE TOP OF THE BLOCK BARRIER.
- 14. IF THE STONE FILTER BECOMES CLOGGED WITH SEDIMENT SO THAT IT NO LONGER ADEQUATELY PERFORMS ITS FUNCTION, THE STONE MUST BE PULLED AWAY FROM THE BLOCKS, CLEANED AND REPLACED.


MANUFACTURED SEDIMENT BARRIERS

15. MANUFACTURED SEDIMENT BARRIERS ARE NOW AVAILABLE THAT COULD BE FUNCTIONALLY EQUIVALENT TO THE BARRIERS LISTED ABOVE. THESE MEASURES ARE ACCEPTABLE AS LONG AS THEY ARE INSTALLED, USED, AND MAINTAINED AS SPECIFIED BY THE VENDOR OR MANUFACTURER, AND PREVENT SEDIMENT FROM ENTERING THE STORM DRAIN SYSTEM. IF SUCH PRODUCTS FAIL TO PERFORM THE REQUIRED SEDIMENT TRAPPING FUNCTION, THEY SHALL BE REMOVED AND REPLACED WITH AN EFFECTIVE ALTERNATIVE BARRIER.

TEMPORARY STORM DRAIN







SEDIMENT TRAPS AND SEDIMENT BASINS WILL BE INSPECTED FOR DEPTH OF SEDIMENT, AT A MINIMUM SEDIMENT WOULD BE REMOVED AND TRAP RESTORED TO ITS ORIGINAL SIZE WHEN SEDIMENT REACHES 1/2 OF THE ORIGINAL SIZE CLEAN AT 12"-CHECK

RIP-RAP STONE DAM B" MIN. DIMENSION DEPTH MARKER SEDIMENT TRAP

1. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER, THEY SHALL BE OVERLAPPED BY

. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP

Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH

PH: 603-387-8688

DATE: OCTOBER 2, 2019 DR. BY: JR CK. BY: JR JOB NO. _____ SHEET NO. 7 OF 10

SCALE: NTS

CLASS

CLASS C

CLASS C

CLASS C

CLASS C


DETAILS SITE PLAN TAX PARCEL 4 LOT 150C & E **DOVER ROAD** CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

DATE DESCRIPTION DWN BY CK BY ADDRESS NHDES AOT COMMENTS 03/05/20 ADDRESS NHDES AOT COMMENTS ADDRESS NHDOT AND TOWN COMMENTS

REVISIONS

NOT TO SCALE

Developer Mal-Mar, LLC 20 Summit Avenue, Derry, NH



- 1. DURING THE GROWING SEASON (APRIL 15 SEPTEMBER 15) USE MATS OR MULCH AND NETTING ON SLOPES 15% OR GREATER AND ANY DISTURBED SOIL WITHIN 100 FEÉT OF LAKES, STREAMS AND OOWETLANDS.
- 2. DURING THE LATE FALL AND WINTER (SEPTEMBER 15 APRIL 15) USE HEAVY GRADE MATS ON ALL AREAS NOTED ABOVE PLUS USE LIGHTER GRADE MATS OR MULCH AND NETTING ON SLOPES GREATER THAN 8% THERE MAY BE CASES WHERE MATS WILL BE NEEDED ON SLOPES FLATTER THAN 8%, DEPENDING ON SITE CONDITIONS AND THE LENGTH OF THE SLOPE.
- 3. INSTALL MATS AND STAPLE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.

MAINTENANCE REQUIREMENTS

- 4. ALL BLANKET AND MATS SHOULD BE INSPECTED WEEKLY DURING THE CONSTRUCTION PERIOD, AND AFTER ANY RAINFALL EVENT EXCEEDING 1/2 INCH IN A 24-HOUR PERIOD.
- 5. ANY FAILURE SHOULD BE REPAIRED IMMEDIATELY. IF WASHOUT OF THE SLOPE, DISPLACEMENT OF THE MAT. OR DAMAGE TO THE MAT OCCURS, THE AFFECTED SLOPE SHALL BE REPAIRED AND RESEEDED, AND THE AFFECTED AREA OF MAT SHALL BE RE-INSTALLED OR REPLACED.

SPECIFICATIONS SITE PREPARATION:

GRADE AND SHAPE AREA OF INSTALLATION.

- 7. REMOVE ALL ROCKS, CLODS, TRASH, VEGETATIVE OR OTHER OBSTRUCTIONS SO THAT THE INSTALLED BLANKETS WILL HAVE DIRECT CONTACT WITH THE SOIL.
- 8. PREPARE SEEDBED BY LOOSENING 2-3 INCHES OF TOPSOIL ABOVE FINAL GRADE.
- 9. INCORPORATE AMENDMENTS, SUCH AS LIME AND FERTILIZER, INTO SOIL ACCORDING TO SOIL TEST AND THE SEEDING PLAN.

- 10. SEED AREA BEFORE BLANKET INSTALLATION FOR EROSION CONTROL AND RE-VEGETATION. SEEDING AFTER MAT INSTALLATION IS OFTEN SPECIFIED FOR TURF REINFORCEMENT APPLICATION. WHEN SEEDING PRIOR TO BLANKET INSTALLATION, ALL CHECK SLOTS AND OTHER AREAS DISTURBED DURING INSTALLATION MUST BE
- 11. WHERE SOIL FILLING IS SPECIFIED, SEED THE MATTING AND THE ENTIRE DISTURBED AREA AFTER INSTALLATION AND PRIOR TO FILLING THE MAT WITH SOIL.

INSTALLING AND ANCHORING BLANKETS:

- 12. BLANKETS SHALL BE INSTALLED AND ANCHORED PER THE MANUFACTURER'S SPECIFICATIONS.
- 13. ENSURE COMPLETE CONTACT OF THE PROTECTION MATTING WITH THE SOIL.


- 14. BLANKETS SHALL BE INSTALLED ON SLOPES PER THE MANUFACTURER'S SPECIFICATIONS. IF THE MANUFACTURER'S INSTRUCTIONS DIFFER FROM THOSE LISTED BELOW, THE MANUFACTURER'S INSTRUCTIONS
- 15. BEGIN AT THE TOP OF THE SLOPE BY ANCHORING THE BLANKET IN 6" DEEP X 6" WIDE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING.
- 16. ROLL THE BLANKETS (A.) DOWN OR (B.) HORIZONTALLY ACROSS THE SLOPE.
- 17. THE EDGES OF PARALLEL BLANKETS MUST BE STAPLED WITH APPROXIMATELY 6" OVERLAP.
- 18. WHEN BLANKETS MUST BE SPLICED DOWN THE SLOPE, PLACE BLANKETS END OVER END (SHINGLE STYLE) WITH APPROXIMATELY 6" OVERLAP. STAPLE THROUGH OVERLAPPED AREA, APPROXIMATELY 12"

TEMPORARY EROSION CONTROL BLANKET ON SLOPES

NOT TO SCALE

TEMPORARY EROSION CONTROL BLANKETS NHFG WILDLIFE FRIENDLY REQUIREMENTS

- THE ELIMINATION OF PLASTIC OR 'BIODEGRADABLE PLASTIC' EROSION CONTROL NETTING IS REQUIRED AS THESE ARE KNOWN SOURCE OF ENTRAPMENT AND MORTALITY TO PROTECTED SNAKES AND TURTLES.
- 2. SEVERAL 'WILDLIFE FRIENDLY' OPTIONS SUCH AS WOVEN ORGANIC MATERIAL (E.G., COCO MATTING) OR THE USE OF EROSION CONTROL BERM OKAY
- 3. ACCEPTABLE MATERIALS INCLUDE NORTH AMERICAN GREEN C125BN OR EAST COAST EROSION CONTROL BLANKET ECC-2B BOTH ARE BIODEGRADABLE WITH A COCONUT FIBER MATRIX AND JUTE NETTING



CONSIDERATIONS

- 1. DURING THE GROWING SEASON (APRIL 15 SEPTEMBER 15) USE MATS OR MULCH AND NETTING ON THE BASE OF GRASSED WATERWAYS.
- 2. DURING THE LATE FALL AND WINTER (SEPTEMBER 15 APRIL 15) USE HEAVY GRADE MATS ON SIDE SLOPES OF GRASSED WATERWAYS.
- 3. INSTALL MATS AND STAPLE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.

- 4. ALL BLANKET AND MATS SHOULD BE INSPECTED WEEKLY DURING THE CONSTRUCTION PERIOD, AND AFTER ANY RAINFALL EVENT EXCEEDING 1/2 INCH IN A 24-HOUR PERIOD.
- 5. ANY FAILURE SHOULD BE REPAIRED IMMEDIATELY. IF WASHOUT OF THE SLOPE, DISPLACEMENT OF THE MAT, OR DAMAGE TO THE MAT OCCURS, THE AFFECTED SLOPE SHALL BE REPAIRED AND RESEEDED, AND THE AFFECTED AREA OF MAT SHALL BE RE-INSTALLED OR REPLACED.

<u>SPECIFICATIONS</u>

GRADE AND SHAPE AREA OF INSTALLATION.

- 7. REMOVE ALL ROCKS, CLODS, TRASH, VEGETATIVE OR OTHER OBSTRUCTIONS SO THAT THE INSTALLED BLANKETS WILL HAVE DIRECT CONTACT WITH THE SOIL.
- 8. PREPARE SEEDBED BY LOOSENING 2-3 INCHES OF TOPSOIL ABOVE FINAL GRADE.
- 9. INCORPORATE AMENDMENTS, SUCH AS LIME AND FERTILIZER, INTO SOIL ACCORDING TO SOIL TEST AND THE SEEDING PLAN.

10. SEED AREA BEFORE BLANKET INSTALLATION FOR EROSION CONTROL AND RE-VEGETATION. SEEDING AFTER MAT INSTALLATION IS OFTEN SPECIFIED FOR TURF REINFORCEMENT APPLICATION. WHEN SEEDING PRIOR TO BLANKET INSTALLATION, ALL CHECK SLOTS AND OTHER AREAS DISTURBED DURING INSTALLATION MUST BE

11. WHERE SOIL FILLING IS SPECIFIED, SEED THE MATTING AND THE ENTIRE DISTURBED AREA AFTER INSTALLATION AND PRIOR TO FILLING THE MAT WITH SOIL.

INSTALLING AND ANCHORING BLANKETS:

- 12. BLANKETS SHALL BE INSTALLED AND ANCHORED PER THE MANUFACTURER'S SPECIFICATIONS.
- 13. ENSURE COMPLETE CONTACT OF THE PROTECTION MATTING WITH THE SOIL.

INSTALLATION IN CHANNELS:

- 14. BLANKETS SHALL BE INSTALLED IN CHANNELS PER THE MANUFACTURER'S SPECIFICATIONS. IF THE MANUFACTURER'S INSTRUCTIONS DIFFER FROM THOSE LISTED BELOW, THE MANUFACTURER'S INSTRUCTIONS
- 15. BEGIN AT THE OUTLET OF THE CHANNEL BY ANCHORING THE BLANKET IN A 6" DEEP X 6" WIDE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING.
- 16. ROLL CENTER BLANKET IN DIRECTION OF THE INLET END OF THE CHANNEL.
- 17. PLACE BLANKETS END OVER END (SHINGLE STYLE) WITH A 6" OVERLAP. USE A DOUBLE ROW OF STAGGERED STAPLES 4" APART TO SECURE BLANKETS.
- 18. FULL LENGTH EDGE OF BLANKETS AT TOP OF SIDE SLOPES MUST BE ANCHORED IN 6" DEEP X 6" WIDE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING.
- 19. BLANKETS ON SIDE SLOPES MUST BE OVERLAPPED 4" OVER THE CENTER BLANKET AND STAPLED.
- 20. IN HIGH FLOW CHANNEL APPLICATIONS, A STAPLE CHECK SLOT IS RECOMMENDED AT 30 TO 40 FOOT INTERVALS. USE A ROW OF STAPLES 4" APART OVER ENTIRE WIDTH OF THE CHANNEL. PLACE A SECOND ROW 4" BELOW THE FIRST ROW IN A STAGGERED PATTERN.
- 21. THE TERMINAL END OF THE BLANKETS MUST BE ANCHORED IN A 6" DEEP X 6" WIDE TRENCH. BACKFILL AND COMPACT THE TRENCH AFTER STAPLING.

TEMPORARY EROSION CONTROL BLANKET FOR CHANNELS

NOT TO SCALE

TEMPORARY & PERMANENT MULCHING

- . WITHIN 100 FEET OF STREAMS, WETLANDS AND IN LAKE WATERSHEDS, TEMPORARY MULCH SHOULD BE APPLIED WITHIN 7 DAYS OF EXPOSING SOIL OR PRIOR TO ANY STORM EVENT.
- 2. AREAS THAT HAVE BEEN TEMPORARILY OR PERMANENTLY SEEDED SHOULD BE MULCHED IMMEDIATELY FOLLOWING SEEDING. 3. AREAS THAT CANNOT BE SEEDED WITHIN THE GROWING SEASON SHOULD BE MULCHED FOR OVER-WINTER PROTECTION. THE AREA SHOULD BE SEEDED AT THE BEGINNING OF THE NEXT GROWING SEASON.
- 4. MULCH ANCHORING SHOULD BE USED ON SLOPES WITH GRADIENTS GREATER THAN 5% IN LATE FALL (PAST SEPTEMBER 15), AND OVER-WINTER (SEPTEMBER 15 - MAY 15).
- 5. PERMANENT MULCH CAN BE USED IN CONJUNCTION WITH TREE, SHRUB, VINE, AND GROUND COVER PLANTINGS.

MAINTENANCE REQUIREMENTS

- S ALL TEMPORARY MULCHES MUST BE INSPECTED PERIODICALLY AND IN PARTICULAR AFTER RAINSTORMS. TO CHECK FOR RULL EROSION OR DISPLACEMENT OF THE MULCH. IF LESS THAN 90% OF THE SOIL SURFACE IS COVERED BY MULCH. ADDITIONAL MULCH SHOULD BE IMMEDIATELY APPLIED. NETS MUST BE INSPECTED AFTER RAIN EVENTS FOR DISLOCATION OR FAILURE, IF WASHOUTS OR BREAKAGES OCCUR, REPAIR ANY DAMAGE TO THE SLOPE AND RE-INSTALL OR REPLACE NETTING AS NECESSARY. INSPECTIONS SHOULD TAKE PLACE UNTIL GRASSES ARE FIRMLY ESTABLISHED (85% SOIL SURFACE UNIFORMLY COVERED WITH HEALTHY STAND OF GRASS)
- 7. EROSION CONTROL MIX MULCH USED FOR TEMPORARY STABILIZATION SHOULD BE LEFT IN PLACE. VEGETATION ADDS STABILITY AND SHOULD BE PROMOTED.
- 8. WHERE PERMANENT MULCH IS USED IN CONJUNCTION WITH ORNAMENTAL PLANTINGS, INSPECT PERIODICALLY THROUGHOUT THE YEAR TO DETERMINE IF MULCH IS MAINTAINING COVERAGE OF THE SOIL SURFACE. REPAIR AS NEEDED.
- 9. PERMANENT MULCHED AREAS SHOULD BE INSPECTED AT LEAST ANNUALLY, AND AFTER EACH LARGE RAINFALL (2.5 INCHES OR MORE IN A 24-HOUR PERIOD). ANY REQUIRED REPAIRS SHOULD BE MADE IMMEDIATELY. WHERE EROSION CONTROL MIX HAS BEEN USED, PLACE ADDITIONAL MIX ON TOP OF THE MULCH TO MAINTAIN THE RECOMMENDED THICKNESS. WHEN THE MULCH IS DECOMPOSED, CLOGGED WITH SEDIMENT, ERODED OR INEFFECTIVE, IT MUST BE REPLACED OR REPAIRED.
- 10. IF THE MULCH NEEDS TO BE REMOVED, SPREAD IT OUT INTO THE LANDSCAPE.

SPECIFICATIONS

- GENERAL: 11. APPLY MULCH PRIOR TO A STORM EVENT. THIS IS APPLICABLE IN EXTREMELY SENSITIVE AREAS SUCH AS WITHIN 100 FEET OF LAKES, PONDS, RIVERS, STREAMS, AND WETLANDS. IT WILL BE NECESSARY TO CLOSELY MONITOR WEATHER PREDICTIONS TO HAVE ADEQUATE WARNING OF SIGNIFICANT STORMS.
- 12. MULCHING SHOULD BE COMPLETED WITHIN THE FOLLOWING SPECIFIED TIME PERIODS FROM ORIGINAL SOIL EXPOSURE:

 WITHIN 100 FEET OF RIVERS AND STREAMS, WETLANDS, AND IN LAKE AND POND WATERSHEDS, THE TIME PERIOD SHOULD BE NO GREATER THAN 7 DAYS. THIS 7-DAY LIMIT SHOULD BE REDUCED FURTHER DURING WET WEATHER
- IN OTHER AREAS, THE TIME PERIOD CAN RANGE FROM 14 TO 30 DAYS, THE LENGTH OF TIME VARYING WITH SITE CONDITIONS (SOIL ERODIBILITY, SEASON OF YEAR, EXTENT OF DISTURBANCE, PROXIMITY TO SENSITIVE RESOURCES) AND THE POTENTIAL IMPACT OF EROSION ON ADJACENT AREAS. OTHER STATE OR LOCAL RESTRICTIONS MAY ALSO APPLY.
- 13. THE CHOICE OF MATERIALS FOR MULCHING SHOULD BE BASED ON SITE CONDITIONS, SOILS, SLOPE, FLOW CONDITIONS, AND
- HAY OR STRAW MULCHES 14. ORGANIC MULCHES INCLUDING HAY AND STRAW SHOULD BE AIR-DRIED, FREE OF UNDESIRABLE SEEDS AND COARSE
- 15. APPLICATION RATE SHOULD BE 2 BALES (70-90 POUNDS) PER 1000 SQUARE FEET OR 1.5 TO 2 TONS (90-100 BALES) PER ACRE TO COVER 75 TO 90 % OF THE GROUND SURFACE.
- 16 HAY OR STRAW MULCH SHOULD BE ANCHORED TO PREVENT DISPLACEMENT BY WIND OR FLOWING WATER, USING ONE OF THE FOLLOWING METHODS: · NETTING: INSTALL JUTE, WOOD FIBER, OR BIODEGRADABLE PLASTIC NETTING OVER HAY OR STRAW TO ANCHOR IT TO THE SOIL SURFACE. INSTALL NETTING MATERIAL ACCORDING TO MANUFACTURER'S RECOMMENDATION. NETTING SHOULD BE USED JUDICIOUSLY, AS WILDLIFE CAN BECOME ENTANGLED IN THE MATERIALS. - TACKIFIER: APPLY POLYMER OR ORGANIC TACKIFIER TO ANCHOR HAY OOOR STRAW MULCH. APPLICATION RATES VARY BY MANUFACTURER: TYPICALLY 40-60 LBS/ACRE FOR POLYMER MATERIAL, AND 80-120 LBS/ACRE FOR ORGANIC MATERIAL LIQUID MULCH BINDERS ARE ALSO TYPICALLY APPLIED HEAVIER AT EDGES, IN VALLEYS, AND AT CRESTS
- 17. WHEN MULCH IS APPLIED TO PROVIDE PROTECTION OVER WINTER (PAST THE GROWING SEASON), IT SHOULD BE APPLIED TO A DEPTH OF FOUR INCHES (150-200 POUNDS OF HAY OR STRAW PER 1000 SQUARE FEET, OR DOUBLE STANDARD APPLICATION RATE). SEEDING CANNOT GENERALLY BE EXPECTED TO GROW UP THROUGH THIS DEPTH OF MULCH AND WILL BE SMOTHERED. IF VEGETATION IS DESIRED, THE MULCH WILL NEED TO BE REMOVED IN THE SPRINGTIME AND THE AREA SEEDED AND MULCHED.

WOOD CHIPS OR BARK: 18. WOOD CHIPS OR GROUND BARK SHOULD BE APPLIED TO A THICKNESS OF 2 TO 6 INCHES.

- 19 WOOD CHIPS OR GROUND BARK SHOULD BE APPLIED AT A RATE OF 10 TO 20 TONS PER ACRE OR 460 TO 920 POUNDS PER 1,000 SQUARE FEET.
- <u>EROSION CONTROL MIX:</u>
 20. EROSION CONTROL MIX CAN BE MANUFACTURED ON OR OFF THE PROJECT SITE. IT MUST CONSIST PRIMARILY OF ORGANIC MATERIAL, SEPARATED AT THE POINT OF GENERATION, AND MAY INCLUDE SHREDDED BARK, STUMP GRINDINGS, COMPOSTED BARK, OR ACCEPTABLE MANUFACTURED PRODUCTS. WOOD AND BARK CHIPS, GROUND CONSTRUCTION DEBRIS OR REPROCESSED WOOD PRODUCTS WILL NOT BE ACCEPTABLE AS THE ORGANIC COMPONENT OF THE MIX.
- 21. COMPOSITION OF THE EROSION CONTROL MIX SHOULD BE AS FOLLOWS: FROSION CONTROL MIX SHOULD CONTAIN A WELL-GRADED MIXTURE OF PARTICLE SIZES AND MAY CONTAIN ROCKS LESS THAN 4" IN DIAMETER. EROSION CONTROL MIX MUST BE FREE OF REFUSE, PHYSICAL CONTAMINANTS, AND MATERIAL TOXIC TO PLANT GROWTH. THE MIX COMPOSITION SHOULD MEET THE FOLLOWING STANDARDS:
- THE ORGANIC MATTER CONTENT SHOULD BE BETWEEN 25 AND 65%, DRY WEIGHT BASIS. - PARTICLE SIZE BY WEIGHT SHOULD BE 100% PASSING A 3" SCREEN, 90% TO 100% PASSING A 1-INCH SCREEN, 70%
- TO 100% PASSING A 0.75-INCH SCREEN, AND A MAXIMUM OF 30% TO 75%, PASSING A 0.25-INCH SCREEN. THE ORGANIC PORTION NEEDS TO BE FIBROUS AND ELONGATED.
- THE MIX SHOULD NOT CONTAIN SILTS, CLAYS OR FINE SANDS.
- SOLUBLE SALTS CONTENT SHOULD BE < 4.0 MMHOS/CM. THE PH SHOULD BE BETWEEN 5.0 AND 8.0.
- 22. THE BARRIER MUST BE PLACED ALONG A RELATIVELY LEVEL CONTOUR. IT MAY BE NECESSARY TO CUT TALL GRASSES OR WOODY VEGETATION TO AVOID CREATING VOIDS AND BRIDGES THAT WOULD ENABLE FINES TO WASH UNDER THE BARRIER THROUGH THE GRASS BLADES OR PLANT STEMS.
- 23. THE BARRIER MUST BE A MINIMUM OF 12" HIGH, AS MEASURED ON THE UPHILL SIDE OF THE BARRIER, AND A MINIMUM OF

WINTER CONSTRUCTION NOTES

- ALL PROPOSED VEGETATED AREAS WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCT. 15TH, OR WHICH ARE DISTURBED AFTER OCT. 15TH, SHALL BE STABILIZED BY SEEDING AND INSTALLING EROSION CONTROL BLANKETS ON SLOPES GREATER THAN 3:1, AND SEEDING AND PLACING 3 TO 4 TONS OF MULCH PER ACRE, SECURED WITH ANCHORED NETTING ELSEWHERE. THE INSTALLATION OF EROSION CONTROL BLANKETS OR MULCH AND NETTING SHALL NOT OCCUR OVER ACCUMULATED SNOW OR ON FROZEN GROUND AND SHALL BE COMPLETED IN ADVANCE OF THAW OR SPRING MELT EVENTS.
- ALL DITCHES OR SWALES WHICH DO NOT EXHIBIT A MINIMUM OF 85% VEGETATIVE GROWTH BY OCT. 15TH, OR WHICH ARE DISTURBED AFTER OCT. 15TH, SHALL BE STABILIZED TEMPORARILY WITH STONE OR EROSION CONTROL BLANKETS APPROPRIATE FOR THE DESIGN FLOW CONDITIONS.
- AFTER OCTOBER 15TH, INCOMPLETE ROAD OR PARKING SURFACES, WHERE WORK HAS STOPPED FOR THE WINTER SEASON, SHALL BE PROTECTED WITH A MINIMUM OF 3 INCHES OF CRUSHED GRAVEL PER NHDOT ITEM 304.3.

DATE

GN-4: VEGETATION STABILIZATION NOTES

ALL VEGETATION STABILIZATION SHALL BE IN ACCORDANCE WITH USDA NRCS "VEGETATING NEW HAMPSHIRE SAND and GRAVEL PITS", IN ADDITION TOO "BEST MANAGEMENT PRACTICES FOR ROUTINE ROADWAY MAINTENANCE ACTIVITIES IN NEW HAMPSHIRE". LATEST EDITIONS.

PARK SEED TYPE 15 SHALL NORMALLY BE USED ON LOAM AREAS. THIS SEED MIXTURE SHALL CONFORM TO TABLE 1 UNLESS AMENDED BY THE PROJECT ENGINEER TO SUIT **ACTUAL FIELD CONDITIONS**

	TA	BLE 1	
(IND OF SEED	MINIMUM	MINIMUM	POUNDS/ACRE
	PURITY (%)	GERMINATION (%)	
CREEPING FESCUE	96	85	40
PERENNIAL RYEGRASS	98	90	50
CENTUCKY BLUEGRASS	97	85	25
REDTOP	95	80	5
		TC	TAI 120

SLOPE SEED TYPE 44 SHALL NORMALLY BE USED FOR ALL SLOPE WORK, and SHALL CONFORM TO TABLE 2 UNLESS AMENDED BY THE DESIGN ENGINEER TO SUIT ACTUAL FIELD CONDITIONS.

	<u>TA</u>	ABLE 2	
KIND OF SEED	MINIMUM	MINIMUM	POUNDS/ACRE
	PURITY (%)	GERMINATION (%)	
CREEPING RED FESCUE	96	85	35
PERENNIAL RYEGRASS	98	90	30
REDTOP	95	80	5
ALSIKE CLOVER	97	90	5
BIRDSFOOT TREFOIL	98	80	5
		TO	ΤΔΙ 80

SEEDING SEASON:

1. SEEDBED PREPARATION ALL AREAS TO BE SEEDED SHALL BE A REASONABLY FIRM, BUT FRIABLE.

- SURFACE and SEEPAGE WATER SHOULD BE DRAINED OR DIVERTED FROM THE SITE TO PREVENT DROWNING OR WINTER KILLING.
- C. THE SEEDBED SHOULD BE LEFT IN A REASONABLY FIRM and SMOOTH CONDITION, FOLLOWING **SEEDING OPERATIONS**
- D. ALL AREAS TO BE SEEDED SHALL MEET THE SPECIFIED GRADES, AS SPECIFIED ON THE APPROVED PLAN.
- E. ALL VEGETATION SHALL BE INSPECTED ANNUALLY FOR UNHEALTHY or DEAD AREAS. ANY and ALL SUCH AREAS ARE TO BE REPAIRED or REPLACED IN KIND.

2. ESTABLISHING A STAND

- LIME AND FERTILIZER SHOULD BE APPLIED PRIOR TO OR AT THE TIME OF SEEDING AND INCORPORATED INTO THE SOIL. KINDS AND AMOUNTS OF LIME AND FERTILIZER SHOULD BE BASED ON EVALUATION OF SOIL TESTS. WHEN A SOIL TEST IS NOT AVAILABLE, THE
 - FOLLOWING MINIMUM AMOUNTS SHOULD BE APPLIED: - AGRICULTURAL LIMESTONE: 2 TONS PER ACRE OR 0.09 LBS. PER SQ. FT.

 - NITROGEN (N): 50 LBS. PER ACRE OR 1.1 LBS. PER 1000 SQ. FT. - PHOSPHATE (P2O5): 100 LBS. PER ACRE OR 2.2 LBS. PER 1000 SQ. FT.
 - POTASH (K₂O): 100 LBS. PER ACRE OR 2.2 LBS. PER 1000 SQ. FT. (NOTE: THIS IS THE EQUIVALENT OF 500 LBS. PER ACRE OF 10-20-20 FERTILIZER OR 1,000 LBS. PER
- B. SEED SHOULD BE SPREAD UNIFORMLY BY THE METHOD MOST APPROPRIATE FOR THE SITE. METHODS INCLUDE BROADCASTING, DRILLING, AND HYDROSEEDING. WHERE BROADCASTING IS USED, COVER SEED WITH 0.25 INCH O SOIL OR LESS, BY CULTIPACKING OR RAKING.

- HAY, STRAW, OR OTHER MULCH, WHEN NEEDED, SHOULD BE APPLIED IMMEDIATELY AFTER
- MULCH WILL BE HELD IN PLACE USING TECHNIQUES FROM THE "BEST MANAGEMENT PRACTICE FOR MULCHING", AS SHOWN IN, "STORMWATER MANAGEMENT AND SEDIMENTATION CONTROL HANDBOOK FOR URBAN AND DEVELOPING AREAS IN NEW HAMPSHIRE".

4. MAINTENANCE TO ESTABLISH A STAND

ACRE OF 5-10-10)

- A. PLANTED AREAS SHOULD BE PROTECTED FROM DAMAGE BY FIRE, GRAZING, TRAFFIC, AND DENSE WEED GROWTH.
- B. FERTILIZATION WILL BE PERFORMED ANNUALLY IN ACCORDANCE WITH NOTE 2A..
- IN WATERWAYS, CHANNELS, OR SWALES WHERE UNIFORM FLOW CONDITIONS ARE ANTICIPATED, OCCASIONAL MOWING or TRIMMING WILL BE PERFORMED ANNUALLY TO CONTROL GROWTH.
- ALL VEGETATION SHOULD BE INSPECTED REGULARLY and AFTER EVERY MAJOR RAIN EVENT (> 5"/24 hr). DAMAGED AREAS SHOULD BE REPAIRED AND RE-VEGETATED IMMEDIATELY.



Developer Mal-Mar, LLC 20 Summit Avenue, Derry, NH


SITE PLAN TAX PARCEL 4 LOT 150C & E DOVER ROAD CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE


DETAILS

DESCRIPTION DWN BY CK BY ADDRESS NHDES AOT COMMENTS ADDRESS NHDOT AND TOWN COMMENTS

Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688

SCALE: NTS DATE: OCTOBER 2, 2019 DR. BY: JR CK. BY: JR JOB NO. _____ SHEET NO. 8 OF 10





CHICHESTER PLANNING BOARD SITE PLAN REVIEW APPLICATION

Owner of Record: CHICHESTER COMMONS Map	Number: 4 Lot Number: 161A , 161
Address: 114-114A DOYER RD, CHICH	•
Daytime Phone Number: 739-9004 Evening Ph	none Number: 724 - 9010
Prepared by: JONATHAN HALLE/ WARE	LENSTREET ARCHITECTS
Address: 142 W. PARISH RD CONCOR	D, NH 03303
Daytime Phone Number: 225 - 0640 Evening Ph	none Number: 224-9010
1. Road Location: RT 4	Address of the second of the s
2. Property Located in the CV-COMM.VILLAG	Ezone.
3. Land is in open space (current use):YES;	NO
4. Area of entire tract: 3.532 (acres) BOTH	PARCELS 5.549 Ac.
Portion to be utilized: (acres or square f	feet)
5. Describe planned use: AMEND PREVIOUS PLANNING BOAR 14 UNIT (II-ONE BEDROOM AND 3-TWOB REDUCE TO 13 UNIT (9-ONE BEDR TOTAL BEDROOM COUNT OF 17 TO 1	EDROWN PROJECT TO
The applicant agrees that he/she is familiar with the Sit Chichester and the Laws of the State of New Hampshire making this application, has complied with the same.	te Plan Regulations of the Town of governing site plan review, and in
Joneshim Halen	03-14-2020
Property Owner or Applicant	Date

Final: 11-7-2019



Town of Chichester

Office of the Planning Board

54 Main Street Chichester, New Hampshire 03258 (603) 798-5350 Fax (603) 798-3170

Permission to Inspect
I, JONATHAN HALLE, property owner of Map 9 Lot 16/A 16/
on 114 - 114 A POVER RD, in the town of Chichester, NH do hereby grant my
permission for the Town Engineer to inspect site improvements or plans when the Chichester
Planning Board requests.
I understand that all cost of the employment of said engineer for inspection(s), test(s) or
review shall be paid by me; prepaid in an escrow account held and managed by the Town
Treasurer. Such funds shall be expended upon final billing by said engineer and any remainin
funds to include earned interest shall be returned to me.
Signature Owner of Record Date
Witness Date

CHECKLIST - SITE PLAN REVIEW

In cases where not all items are applicable, draw a line through the items which are not applicable.

CHICHESTER HOUSING

APPLICABLE	INCLUDED)	
(Y/N)	(Y/N)	<u>INITIALS</u>	
<u> </u>	Y	JH	Three copies of the completed application and checklist
<u>Y</u>	<u>Y</u>	74	2. Site plan: 22" by 34" sheet size maximum, scale not less than 1" =100', match lines where needed, boundaries, water courses & bodies of water, trees and other vegetation, topography at 2' intervals to USGS datum, existing and proposed contours and finished grade elevations and other pertinent features, date, title, graphic scale, north arrow, location map, name & address of developer/applicant, designer/engineer, owner of record.
<u>Y</u> _	Y	JH	 List of names and addresses of abutters and owners of land within 200' of any property line. (YOU MAY NOT ABUT YOURSELF)
<u> </u>	Y	JH	4. The appropriate fee
<u> </u>	<u>Y</u>	JH	Plan of all buildings depicting their type, size, and location (setbacks)
<u> </u>	Y	JH	6. An elevation view or photo of all buildings
<u> </u>	Y	JH	7. Layout of off-street parking and loading
<u> </u>	<u>Y</u> -	JH	8. Ingress-egress of site and depiction of streets both within and adjacent to site
_Y	Y	HL	9. Solid waste disposal facilities
<u> </u>	Y	JH 1	 .0. Location, size, and design of signs and advertising or instructional devices
Y	<u>Y</u>	JH 1	1. Location, type, direction, and illuminated area of outside lighting
Y	Υ	1.11	2. Other required exhibits or data, any permits specific to site.
<u> </u>	Y	1.11	3. Permanent first floor elevation of proposed buildings

Final: 11-7-2019

CHECKLIST - SITE PLAN REVIEW - CONTINUED

<u> </u>	<u>Y</u>	14. Existing water supply and sewage disposal facilities on the site
		and within 200' of the site, proposed water and sewage facilities, and provisions for expansion of water and sewage facilities
<u> </u>	<u>Y</u>	15. Location, elevation, and layout of surface drainage facilities
<u>Y</u>	_Y	16. Existing and proposed landscaping and open space areas and
~/		treatment
<u> </u>	<u> </u>	17. Gas, electric, telephone, CATV utility lines
<u> </u>	_Y	
\		
	<u> </u>	19. Description or depiction of proposed grading, filling, or other site preparation
	<u> </u>	20. Existing and proposed buffers
<u> </u>	_Y_	21. Existing and proposed screening
	_Y	22. Sidewalks, access, loading & parking
<u> </u>	Y	23. Erosion and sedimentation control plan
N	N	24. Flood plain areas
~	Y	25. Town Engineer authorization
		26. Wetlands Setbacks.

CHICHESTER HOUSING

114A DOVER ROAD CHICHESTER, NH 03258



CHICHESTER HOUSING, LLC

SPONSOR: RISE AGAIN C/O: LORI & JONATHAN HALLE 142 W. PARISH ROAD CONCORD, NH 03303 P. (603) 738-9004

HUTTER CONSTRUCTION, CORP.

PROJECT MANAGER: DAVE LAGE PO BOX 257, RT. 124 NEW IPSWICH, NH 03071 P. (603) 878-2300


WARRENSTREET ARCHITECTS, INC.

ATTN: JONATHAN HALLE, AIA PLANNERS, ARCHITECTS, LANDSCAPE ARCHITECTS, INTERIOR DESIGNERS 27 WARREN STREET, CONCORD, NH 03301 P. (603) 225-0640

CIVIL	SURVEY	ARCHITECTURE	STRUCTURAL	MECHANICAL/PLUMBIN	NG ELECTRICAL	OTHER	PROJECT:				
BEDFORD DESIGN CONSULTANTS 177 EAST INDUSTRIAL PARK DR. MANCHESTER, NH 03109 P. (603) 622-5533	RICHARD D. BARTLETT & ASSOCIATES 214 N. STATE ST. CONCORD NH, 03301 P. (603) 225-6770	WARRENSTREET ARCHITECTS, INC. 27 WARREN STREET CONCORD, NH 03301 P. (603) 225-0640 F. (603) 225-0621	TF MORAN, INC. 48 CONSTITUTION DRIVE BEDFORD, NH 03110 P. (603) 472-4488	DESIGN DAY MECHANICALS, INC. PO BOX 447 NEW IPSWICH, NH 03071 P. (603) 269-7253	SWIFTCURRENT ENGINEERING 10 FOREST FALLS DRIVE, #4B YARMOUTH, ME 04096 P. (207) 847-9280	NHHFA CONSTRUCTION STANDARDS 2020	CHICHESTER HOUSING PROJECT NUMBER: 3393				
CONDOMINIUM SUBDIVISION / SITE PLAN EXISTING CONDITION PLAT CONDOMINIUM SUBDIVISION / SITE PLAN	1 EXISTING CONDITIONS PLAT Located in Civil Set)	1 CONSTRUCTION NOTES, LOCUS PLAN & CONSTRUCTION SIGN A001 ADA, CONVERSIONS, SYMBOLS, SIGNAGE & ABBREVIATIONS A002 CODE REVIEW A003	GENERAL STRUCTURAL NOTES GENERAL STRUCTURAL NOTES CONT. FOUNDATION PLAN	S001 HVAC BASEMENT & FIRST FLOOR PLAN HVAC 2ND S002 FLOOR & ATTIC PLAN HVAC COMMON AREA S101 HAVC ENLARGED APRTMENT PLAN	M101 ELECTRICAL GENERAL NOTES & LEGEND M102 ELECTRICAL POWER & SYSTEMS PLAN - BASEMENT & FIRST FLOOR M103 ELECTRICAL POWER & SYSTEMS PLAN - SECOND FLOOR & ROOF	BY REFERENCE - SEE SPECIFICATIONS =100 =101	ISSUE:				
GRADING PLAN GRADING PLAN UTILILTY PLAN NHDOT CURBCUT PLAN INDIVIDUAL SEWERAGE SYSTEM SEPTIC PLAN LANDSCAPE PLAN CONSTRUCTION DETAILS CONSTRUCTION DETAILS CONSTRUCTION DETAILS CONSTRUCTION DETAILS CONSTRUCTION DETAILS CONSTRUCTION DETAILS	3 4 5 6 7 8 9 10 11 12 13 14 15	CODE PLANS & COMPLIANCE LETTERS KEY/SITE PLAN FIRST FLOOR PLAN SECOND FLOOR PLAN BASEMENT FLOOR PLAN A102 BASEMENT FLOOR PLAN A103 ATTIC FLOOR PLAN UNIT TYPE A TYPICALS UNIT TYPE B TYPICALS UNIT TYPE C TYPICALS A113	SECOND FLOOR FRAMING PLAN ROOF FRAMING PLAN TYPICAL FOUNDATION DETAILS TYPICAL FOUNDATION DETAILS FOUNDATION DETAILS TYPICAL FRAMING DETAILS TYPICAL FRAMING DETAILS TYPICAL FRAMING DETAILS FRAMING DETAILS FRAMING DETAILS TYPICAL ROOF FRAMING DETAILS ROOF FRAMING DETAILS	S102 HVAC DETAILS AND LEGENDS HVAC SCHEDULES HVAC SPECIFICATIONS S201 S202 PLUMBING FBSMT & IRST FLOOR PLAN PLUMBING 2ND FLOOR & ATTIC PLAN DOMESTIC WATER BSMT & FIRST FLOOR PLAN DOMESTIC WATER 2ND FLOOR & ATTIC PLAN PLUMBING SCHEDULES PLUMBING SPECIFICATIONS	M104 M105 M106 M107 ELECTRICAL LIGHTING PLAN - BASEMENT, FIRST & SECOND FLOOR ELECTRICAL LIGHTING SCHEDULE ELECTRICAL FIRE ALARM PLAN - BASEMENT, FIRST & SECOND FLOOR ELECTRICAL FIRE ALARM RISER DIAGRAM ELECTRICAL FIRE ALARM PLAN - BASEMENT, FIRST & SECOND FLOOR ELECTRICAL FIRE ALARM PLAN - BASEMENT, FIRST & SECOND FLOOR P103 P104 P105 P106 NOTE: (4) SITE LIGHTS SHOWN ON CIVIL DRAWING 3/15, POLE BASE SHOWN 11/15 AND 'P' FIXTURE CALLED OUT ON E201	E102 E200 E201 E300 E301 E400	ISSUED FOR CONSTRUCTION ISSUE DATE: 02/14/2020				
NOTE: (4) SITE LIGHTS SHOWN ON CIVIL DRAWING 3/15, POLE BASE SHOWN 11/15 AND 'P' FIXTURE CALLED OUT ON E201		FIRST FLOOR REFLECTED CEILING PLAN SECOND FLOOR REFLECTED CEILING PLAN A142 ROOF PLAN A151		WAIVER REQUESTS			REVISIONS:				
SHOWN 11/15 AND P FIXTURE CALLED OUT ON E201		EXTERIOR ELEVATIONS A201 BUILDING SECTIONS A301 BUILDING SECTIONS A302 VERTICAL CIRCULATION SECTIONS & DETAILS & WALL SECTIONS WALL SECTIONS A321 PARTITION TYPES A601	BUILDING SECTIONS A3 BUILDING SECTIONS VERTICAL CIRCULATION SECTIONS & DETAILS & WALL SECTIONS WALL SECTIONS PARTITION TYPES DOOR SCHEDULE, ELEVATIONS & DETAILS A3 BUILDING SECTIONS A3 A3 A4 A5 A6	BUILDING SECTIONS A3 BUILDING SECTIONS VERTICAL CIRCULATION SECTIONS & DETAILS & WALL SECTIONS WALL SECTIONS A3 PARTITION TYPES DOOR SCHEDULE, ELEVATIONS & DETAILS A6					NOTE: THIS PROJECT IS FUNDED THRU NH HOUSING FINANCE AUTHORITY, FEDERAL HOME LOAN BANK OF BOSTON AND LITCH FEDERAL TAX CREDITS AND ARE GOVERNED BY CONSTRUCTION GUIDELINES FOUND IN THE SPECIFICATIONS 1. LIQUIDATED DAMAGES OF \$500/DAY - CM CONTRACT 2. ENERGY STAR MODELING - DESIGN 3. BORINGS AND GEOTECH REPORT - DESIGN 4. ENERGY STAR CERTIFICATION AND BLOWER DOOR TEST - POST CONSTRUCTION 5. 48" PT PLYWOOD AT BASE ALL EXTERIOR WALLS	DITS	REV. DATE CONVINENTS
		WINDOW SCHEDULE, ELEVATIONS & DETAILS & INT. DOOR A603 DETAILS		ALTERNATES							
				 PROVIDE PRICING FOR THE DELETION OF (1) ONE BEDROOM APA TOTAL OF (13) UNITS VS. (14) ALTERNATE MANUFACTURERS WILL BE REVIEWED AT TIME OF CO 	ARTMENT UNIT 107 AND CONVERSION OF UNIT 105 TO A TWO BEDROOM UNIT.		ARCHITECT OF RECORD				
MI 00:47:7 0707000				ALLOWANCES 1. GC TO CARRY CONSTRUCTION CONCRETE AND SOILS TESTING A 2. GC TO CARRY CONSTRUCTION SPECIAL INSPECTIONS ALLOWANG			Supplied to the same of the sa				


CHICHESTER COMMONS CONDOMINIUM SUBDIVISION / SITE PLAN

114 DOVER ROAD CHICHESTER, NH 03258



- A		
1000	PLAN INDEX	<u>IEET NO</u>
	COVER SHEET	1
	EXISTING CONDITIONS PLAN	2
	CONDOMINIUM SUBDIVISION/SITE PLAN	3
	GRADING PLANS	4-5
	UTILITY PLAN	6
	NHDOT CURBCUT PLAN	7
	SEPTIC SYSTEM	8-9
	LANDSCAPE PLAN	10
	DETAIL SHEETS	11-15
	COMMERCIAL CONDO ELEVATIONS & FLOOR PLANS	A100

MULTIFAMILY CONDO ELEVATIONS & FLOOR PLANS A101-A103



NOTES:

1. THE PURPOSE OF THIS PLAN IS TO MERGE TAX MAP 4 LOTS 161 & 161A INTO 1 LOT (TAX MAP 4 LOT 161) AND TO CREATE A CONDOMINIUM CONSISTING OF A MULTIFAMILY RESIDENTIAL UNIT CONSISTING OF 13 DWELLINGS (9—ONE BEDROOM & 4—TWO BEDROOM) AND 7 COMMERCIAL UNITS, LOCATED ON 2 LAND UNITS WITH ASSOCIATED LIMITED COMMON AREAS, AND COMMON AREAS. (SEE NOTE #18)

BK: 3407 PG: 1260

2. OWNERS OF RECORD: TAX MAP 4 LOT 161 CHICHESTER COMMONS, LLC CHICESTER COMMONS, LLC 142 W. PARISH ROAD CONCORD, NH 03303 CONCORD, NH 03303

BK: 3407 PG:1290

- 3. TOTAL AREA OF PARCELS IS 241,713 S.F. (5.549 ACRES)
- 4. PROPERTY ADDRESS: 114 DOVER ROAD
- 5. THE PARCEL IS ZONED (CV) COMMERCIAL VILLAGE DISTRICT

CV REQ.	<u>PROPOSED</u>
2 AC.	5.549 AC.
<i>50</i> ′	<i>582.25</i> '
<i>25'</i>	<i>25'</i>
<i>50'</i>	<i>50'</i>
70%	23%
25%	40%
90'	123'
15'	<i>28.6</i> '
15'	<i>238'</i>
5,000 S.F.	6,790 S.F.
<i>35</i> '	29' FRONT
	39' REAR
90'	90° (EXISTING)
15'	>15 (EXISTING)
15'	>15' (EXISTING)
	24' (EXISTING)
	2 AC. 50' 25' 50' 70% 25% 90' 15' 5,000 S.F. 35'

6. THE EXISTING LOT IS A COMMERCIAL BUILDING AND PARKING.

8. PARKING REQUIREMENTS: (Sec 2.04 VIII.11.j)

- 7. BEDFORD DESIGN CONSULTANTS DID NOT PERFORM ANY FIELD SURVEYS. THIS PLAN USED THE REFERENCED PLAN FOR THE BOUNDARY AND LOCATION OF THE IMPROVEMENTS
- MULTI-FAMILY PARKING 9'x19' SPACES WITH 22' AISLES

 9 ONE BEDROOM DWELLING UNITS @ 2/DWELLING UNIT = 18 SPACES

 4 TWO BEDROOM DWELLING UNITS @ 2.5/DWELLING UNIT = 10 SPACES

 TOTAL REQUIRED = 28 SPACES

 30 SPACES PROVIDED

 (INCLUDING 2 H/C SPACES)

 COMMERCIAL PARKING: 9,400 S.F. @ 1/200 S.F. = 47 SPACES REQUIRED

COMMERCIAL PARKING: 9,400 S.F. © 1/200 S.F. = 47 SPACES REQUIRED

EXISTING SITE 39 SPACES

PROPOSED SITE 42 SPACES

TOTAL FOR LOT REQUIRED 77 SPACES


PROPOSED 72 SPACES (SEE NOTE 16)

- 9. DENSITY: (Sec 2.04 VIII.11.b) MULTIFAMILY 2 ACRES FOR FIRST TWO-FAMILY PLUS 1/2 ACRE FOR EACH ADDITIONAL UNIT = 2 + 0.5(11) = 7.5 ACRES REQUIRED (SEE NOTE 17)
- 10. THIS LOT IS SERVED BY ON-SITE SEPTIC AND WELL.
- 11. THE SUBJECT PROPERTY IS NOT WITHIN THE 100—YR FLOOD PLAIN AS PER THE FLOOD INSURANCE RATE MAP, MERRIMACK COUNTY NEW HAMPSHIRE COMMUNITY PANEL 557 OF 705, MAP NUMBER 33013C0557E, EFFECTIVE DATE APRIL 19, 2010.
- 12. FOR THIS SITE PLAN THE FOLLOWING STATE AND LOCAL PERMITS ARE REQUIRED (COPIES ARE FILED WITH THE PLANNING DEPARTMENT):

 NHDES INDIVIDUAL SEPTIC eCA2018091107

 NHDES SUBDIVISION eSA2018091101

 NHDOT CURBCUT 05—089—0028
- 13. SITE LIGHTING: DOWN CAST CUT-OFF LUMINARIES SHALL BE PROVIDED AS SHOWN ON THE SITE DETAILS AND LIGHTING PLAN IN ACCORDANCE WITH THE TOWN OF KINGSTON CHICHESTER.
- 14. SITE SIGNAGE WILL COMPLY WITH THE CHICHESTER REGULATIONS.



				ă.
4-6-20	REDUCED BUILDING SIZE	MKH	С	
2-19-20	REV. UNIT 8 FOOTPRINT, DUMPSTERS, ACCESS EASE.	JST	В	
8-24-18	PER FUSS & O'NIELL 8-21 REVIEW LETTER	JST	А	
DATE	DESCRIPTION	BY	REV.	

LOCUS MAP

NOT TO SCALE

- 16. THE FOLLOWING WAIVERS WERE GRANTED FROM ZONING ORDINANCE BY PLANNING BOARD ON JULY 12, 2018:

 * SECTION 2.04.F:VI-12 TO PERMIT A BUILDING WITH A FOOTPRINT 9,995 S.F. WHERE ONLY 5.000 S.F. PERMITTED,
- SECTION 2.04.F;VIII—II(h) TO PERMIT A STRUCTURE OF 29 FEET IN THE FRONT AND 39 FEET IN THE REAR WHERE 35 FEET IS REQUIRED.
- SECTION 2.04.F;VI-12 TO PERMIT A COMMERCIAL STRUCTURE OF 10,000 SF WHERE ONLY 5,000 IS PERMITTED.
- 5,000 IS PERMITTED.
 SECTION 2.04,F;VI-10(b) TO ALLOW 72 SPACES WHERE 77 REQUIRED.
 SECTION 2.04F;VI-2 TO ALLOW A 14 UNIT RESIDENTIAL STRUCTURE (11-ONE BEDROOM UNITS) AND 7 UNIT COMMERCIAL STRUCTURE ON A SINGLE LOT.
- 17. ON JULY 12, 2018 THE PLANNING BOARD GRANTED A CONDITIONAL USE PERMIT (CUP) FROM SECTION 2.04.F;11(b) TO ALLOW 14 RESIDENTIAL UNITS (11—ONE BEDROOM & 3—TWO BEDROOM UNITS ON 5.549 ACRE PARCEL OF LAND WHERE 8 ACRES IS REQUIRED.
- 18. ON JULY 12, 2018 THE PLANNING BOARD GRANTED A LOT MERGER OF TAX MAP 4 LOT 161 AND TAX MAP 4 LOT 161A TO BE TAX MAP 4 LOT 161.

19. IF DURING CONSTRUCTION, IT BECOMES APPARENT THAT DEFICIENCIES EXIST IN THE APPROVEL

- DESIGN DRAWINGS, THE OWNER SHALL BE REQUIRED TO CORRECT THE DEFICIENCIES TO MEET THE TOWN OF CHICHESTER REQUIREMENTS TO THE REGULATIONS AT NO EXPENSE TO THE TOWN 20. IF DURING CONSTRUCTION, IT BECOMES APPARENT THAT ADDITIONAL EROSION CONTROL MEASURES ARE REQUIRED TO STOP ANY EROSION ON THE CONSTRUCTION SITE DUE TO ACTUAL
- SITE CONDITIONS, THE CONTRACTOR SHALL BE REQUIRED TO INSTALL THE NECESSARY EROSION PROTECTION AT NO EXPENSE TO THE TOWN.

 21. ALL MATERIALS AND METHODS OF CONSTRUCTION SHALL CONFORM TO THE TOWN OF CHICHESTER SITE PLAN REGULATIONS AND THE LATEST ADDITION OF THE NEW HAMPSHIRE
- DEPARTMENT OF TRANSPORTATION'S STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.

 22. ALL IMPROVEMENTS SPECIFIED ON THESE SITE PLANS SHALL BE CONSTRUCTED, COMPLETED, INSPECTED AND APPROVED BY THE TOWN OF CHICHESTER PRIOR TO ISSUANCE OF A
- CERTIFICATE OF OCCUPANCY. CONTRACTOR SHALL BE RESPONSIBLE FOR SCHEDULING INSPECTIONS AND OBTAINING ALL NECESSARY APPROVALS AND CERTIFICATE OF OCCUPANCY.
- 23. SITE IMPROVEMENTS DEPICTED ON THE PLAN SHALL CONFORM WITH TITLE III OF THE AMERICANS WITH DISABILITIES ACT WITH REGARD TO DIMENSION AND GRADES
- 24. HOURS OF CONSTRUCTION 6:00 A.M. TO 6:00 P.M. MONDAY THROUGH SATURDAY
- 25. PLOWED SNOW FROM THE FACILITIES DRIVEWAY, PARKING LOT AND SIDEWALKS SHALL BE STORED IN THE DESIGNATED AREA SHOWN IN THIS PLAN SET. WHEN SNOW STORAGE AREAS ARE AT CAPACITY, SUBSEQUENT SNOW SHALL BE HAULED OFF SITE AND DISPOSED OF IN AN ENVIRONMENTALLY SOUND FASHION AND IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.
- 26. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING AND DETERMINING THE LOCATION, SIZE AND ELEVATION OF ALL EXISTING UTILITIES SHOWN OR NOT SHOWN ON THESE PLANS. PRIOR TO THE START OF ANY CONSTRUCTION, THE ENGINEER SHALL BE NOTIFIED IN WRITING OF ANY UTILITIES FOUND INTERFERING WITH THE PROPOSED CONSTRUCTION AND APPROXIMATE REMEDIAL ACTION TAKEN BEFORE PROCEEDING WITH THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONTACTING "DIG SAFE" AT LEAST 72 HOURS BEFORE DIGGING.
- 27. THIS PLAN SET CONTAINS 15 SHEETS. SHEET 3 (CONDOMINIUM SUBDIVISION) SHALL BE RECORDED AT THE MERRIMACK COUNTY REGISTRY OF DEEDS. THE ENTIRE SET IS ON FILE AT THE CHICHESTER PLANNING DEPARTMENT.
- 28. NO STORAGE OF LIQUIDS OR HAZARDOUS MATERIALS ON—SITE.
- 29. OWNER TO REMOVE/CONTROL VEGETATION AND FOREVER MAINTAIN AS NECESSARY TO PROVIDE NECESSARY SAFE SIGHT DISTANCE.
- 30. A STORMWATER POLLUTION PREVENTION PLAN (SWPPP) IS REQUIRED FOR ANY NEW CONSTRUCTION ON

APPROVED BY THE PLANNING BOARD OF CHICHESTER, N.H.

DATE CHAIRMAN

TAX MAP 4 LOTS 161 & 161A

CONDOMINIUM SUBDIVISION / SITE PLAN
114 DOVER ROAD
CHICHESTER, NEW HAMPSHIRE 03258

OWNER OF RECORD

CHICHESTER COMMONS, LLC
142 W. PARISH ROAD
CONCORD, NH 03303


SCALE: 1" =	50'	MAY 24, 2018			EET 1 OF 15
DESIGN:	DRAWN:	CHECKED:	FB:	PG:	921-04
GAC	JST	GAC		###	921-04


Bedford Design Consultants Inc.

ENGINEERS AND SURVEYORS

177 East Industrial Park Drive, Manchester, NH 03109
Telephone: (603) 622-5533 Fax: (603) 622-4740

www.bedforddesign.com





WARRENSTREET **ARCHITECTS**

27 Warren Street Concord NH 03301 T 603.225.0640 F 603.225.0621 www.warrenstreet.coop

CHICHESTER HOUSING, LLC

SPONSOR: RISE AGAIN C/O: LORI & JONATHAN HALLE 142 W. PARISH ROAD CONCORD, NH 03303 P. (603) 738-9004

HUTTER CONSTRUCTION, CORP. PROJECT MANAGER: DAVE LAGE PO BOX 257, RT. 124 NEW IPSWICH, NH 03071

P. (603) 878-2300

BEDFORD DESIGN

CONSULTANTS 177 EAST INDUSTRIAL PARK DR. MANCHESTER, NH 03109 P. (603) 622-5533

STRUCTURAL TF MORAN, INC.

48 CONSTITUTION DRIVE BEDFORD, NH 03110 P. (603) 472-4488

MECHANICAL/PLUMBING DESIGN DAY MECHANICALS, INC.

PO BOX 447 NEW IPSWICH, NH 03071 P. (603) 269-7253

ELECTRICAL

SWIFTCURRENT ENGINEERING 10 FOREST FALLS DRIVE, #4B YARMOUTH, ME 04096 P. (207) 847-9280

PROJECT TITLE / ADDRESS:

CHICHESTER HOUSING

114A DOVER ROAD CHICHESTER, NH 03258



SCALE: AS NOTED DWN BY: KL JOB #: 3393

PRINT DATE:

4/6/2020 9:50:58 AM

CHK BY: JH

ISSUE DATE: 4/6/2020

ALTERNATE (13) UNIT


FIRST FLOOR - ALTERNATE (13) UNIT

THE DRAWING AND ITS CONTENT IS THE INTELLECTUAL PROPERTY OF WARRENSTREET ARCHITECTS INC. WITH THE SOLE INTENT TO BUILD THE PROJECT TITLED ABOVE AT ONE LOCATION NOTED HEREIN. THE USE OF THE CONTENT FOR ANY OTHER PURPOSE IS PROHIBITED AND PROTECTED UNDER COPYRIGHT LAW.

Copyright Warrenstreet Architects, Inc. © 1990 - 2020

FIRST FLOOR PLAN (LEVEL OF DISCHARGE)

A101A 1/8" = 1'-0"



WARRENSTREET

ARCHITECTS 27 Warren Street Concord NH 03301

T 603.225.0640 F 603.225.0621 www.warrenstreet.coop

CHICHESTER HOUSING, LLC SPONSOR: RISE AGAIN C/O: LORI & JONATHAN HALLE 142 W. PARISH ROAD CONCORD, NH 03303 P. (603) 738-9004

HUTTER CONSTRUCTION, CORP. PROJECT MANAGER: DAVE LAGE PO BOX 257, RT. 124 NEW IPSWICH, NH 03071

P. (603) 878-2300 CIVIL

BEDFORD DESIGN CONSULTANTS 177 EAST INDUSTRIAL PARK DR. MANCHESTER, NH 03109

P. (603) 622-5533 STRUCTURAL STRUCTURAL

TF MORAN, INC. 48 CONSTITUTION DRIVE BEDFORD, NH 03110 P. (603) 472-4488

MECHANICAL/PLUMBING

DESIGN DAY MECHANICALS, INC. PO BOX 447 NEW IPSWICH, NH 03071 P. (603) 269-7253


ELECTRICAL

SWIFTCURRENT ENGINEERING 10 FOREST FALLS DRIVE, #4B YARMOUTH, ME 04096 P. (207) 847-9280

PROJECT TITLE / ADDRESS:

CHICHESTER HOUSING

114A DOVER ROAD CHICHESTER, NH 03258



SCALE: AS NOTED DWN BY: KL JOB #: 3393

PRINT DATE:

4/6/2020 9:50:59 AM

CHK BY: JH

ISSUE DATE: 4/6/2020

ALTERNATE (13) UNIT

SECOND FLOOR -ALTERNATE (13) UNIT

THE DRAWING AND ITS CONTENT IS THE INTELLECTUAL PROPERTY OF WARRENSTREET ARCHITECTS INC. WITH THE SOLE INTENT TO BUILD THE PROJECT TITLED ABOVE AT ONE LOCATION NOTED HEREIN. THE USE OF THE CONTENT FOR ANY OTHER PURPOSE IS PROHIBITED AND PROTECTED UNDER COPYRIGHT LAW.

Copyright Warrenstreet Architects, Inc. © 1990 - 2020



SITE DEVELOPMENT PLANS

NOTES:

1.) THE SUBJECT PARCEL IS LOT 150C ON THE TOWN OF TAX MAP 4. THE OWNER OF RECORD OF LOT 150C IS MAL-MAR LLC OF 20 SUMMITT AVENUE, DERRY, NH 03038. SEE MCRD V. 2247 P. 434.

2.) THE SUBJECT PARCELS ARE ZONED CI/MF. MINIMUM LOT SIZE IS 2 ACRES. MINIMUM LOT FRONTAGE = 200'. SETBACKS ARE AS FOLLOWS: FRONT = 40' MIN. (90' FROM CENTERLINE OF ROUTE 4, 202 & 9), SIDE = 15' AND REAR = 15', SUBJECT TO EXACT USE. THE SETBACKS SHOWN ARE FOR REFERENCE ONLY AND NEED TO BE VERIFIED WITH THE ZONING COMPLIANCE OFFICER.

3.) THIS PLAN IS THE RESULT OF AN ACTUAL FIELD SURVEY PERFORMED BY THIS OFFICE IN JANUARY TO MARCH OF 2019. I, JOSEPH M. WICHERT, NHLLS #783, CERTIFY THAT THE WORK WAS PREPARED BY ME OR THOSE UNDER MY DIRECT SUPERVISION.

4.) THE INTENT OF THIS PLAN IS TO SHOW THE BOUNDARY OF THE SUBJECT PARCELS AND THE CURRENT CONDITIONS THEREON.

5.) THE SUBJECT PARCELS ARE IN ZONE X (AREAS DETERMINED TO BE OUTSIDE THE 0.2% ANNUAL CHANCE FLOODPLAIN) AS SHOWN ON THE FLOOD INSURANCE RATE MAP, MERRIMACK COUNTY, NEW HAMPSHIRE, MAP NUMBER 33013C0557E, EFFECTIVE DATE APRIL 19, 2010.

6.) THE VERTICAL DATUM IS NAVD 1988 AND THE HORIZONTAL DATUM IS NHSPC 1983/2011. THE DATUM WERE ESTABLISHED USING STATIC GPS OBSERVATIONS PERFORMED BY THIS OFFICE IN AUGUST OF 2018.

7.) THE UTILITY INFORMATION SHOWN IS BASED ON THE ABOVE GROUND LOCATION OF VISIBLE UTILITIES, THE CONTRACTOR NEEDS TO FIELD VERIFY ALL UTILITIES PRIOR TO ANY CONSTRUCTION. THIS OFFICE DOES NOT GUARANTEE THE LOCATION AND ACCURACY OF THE UTILITY DATA. DIG SAFE SHALL BE CONTACTED 72 HOURS PRIOR TO COMMENCING ANY CONSTRUCTION (811).

8.) THE PURPOSE OF THE PLAN SET IS TO SHOW THE PROPOSED IMPROVEMENTS FOR A GRAVEL STORAGE AREA ON THE SUBJECT PARCEL. DRAINAGE, GRADING AND UTILITIES HAVE BEEN INCLUDED

9.) NO CHANGES TO THE PARKING OR BUILDING ARE PROPOSED AS PART OF THIS GRAVEL STORAGE AREA.

10.) WETLANDS WERE DELINEATED BY ASPEN ENVIRONMENTAL CONSULTANTS IN JAN, 7, MARCH 27, AND JULY 29 2019 BY AARON WECHSLER USING THE ARMY CORPS OF ENGINEERS WETLANDS DELINEATION MANUAL, DATED JANUARY 1987.

11.) AN ENVIRONMENTAL MONITOR WILL BE REQUIRED DUE TO THE AREA OF DISTRUBANCE BEING GREATER THAN 5 ACRES. THE MONITOR SHALL ADHERE TO ALL REQUIREMENTS OF ENV-WQ 1505.03(D)

12.) THE GRADING AND DRAINAGE EASEMENTS AS SHOWN SHALL BE RECORDED AT THE REGISTRY OF DEEDS. IN THE EVENT THE LOTS ARE COMBINDED THE EASEMENTS SHALL BE ABANDONDED.

AGENCY APPROVALS:

NHDOT - DRIVEWAY PERMIT APPR # NH DOT DRIVEWAY PERMIT NO. _________ NHDES - ALTERATION OF TERRAIN PERMIT NO.____AoT-1765

PLAN REFERENCES:

1.) "SUBDIVISION OF EDITH TASKER, ROUTE 4, 202 & 9, CHICHESTER, N.H.", DATED AUGUST 1984 AND PREPARED BY SURVEY FIELD SERVICES. MCRD PLAN 8,095.

3.) "STATE OF NEW HAMPSHIRE HIGHWAY DEPARTMENT, PLANS OF PROPOSED FEDERAL AID PROJECT, NO. 179 (2), CENTRAL ROAD, AS-BUILT PLANS, TOWN OF CHICHESTER, COUNTY OF MERRIMACK", DATED 4/03/1940 & ON FILE AT THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION.


4.) CHICHESTER-EPSOM, P7909, WORKSHEET, PLOTTED 7/07/1967 ON FILE AT THE NEW HAMPSHIRE

5.) "STATE OF NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION, CONSTRUCTION PLANS, FEDERAL AID PROJECT, X-A004(170), N.H. PROJECT NO. 29533, US ROUTE 202/4 & NH ROUTE 9. DATED 5/12/2016 & ON FILE AT THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION.



LIST OF DRAWINGS

DWG NO. DESCRIPTION COVER SHEET EXISTING CONDITIONS 3,4 SITE AND GRADING PLAN 5, 6, 7, 8 CONSTRUCTION & EROSION CONTROL DETAILS 9,10 BMP MAINTENANCE SHEETS



NOTE:

1. ALL MATERIALS AND METHODS OF CONSTRUCTION SHALL CONFORM TO THE TOWN OF CHICHESTER REGULATIONS AND THE NEW HAMPSHIRE DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", LATEST EDITION.

2. ELEVATIONS ARE BASED ON NAVD 1988 DATUM.

3. PHYSICAL EVIDENCE OF EXISTING UTILITIES WERE LOCATED ON THE GROUND HOWEVER PRIOR TO ANY CONSTRUCTION IT IS THE CONTRACTOR'S RESPONSIBILITY TO CONTACT DIG-SAFE AND VERIFY ALL UNDERGROUND UTILITY LOCATIONS.

DEPARTMENT OF TRANSPORTATION.



CONTACT DIG SAFE 72 HOURS PRIOR TO CONSTRUCTION

THE LOCATION OF ANY UTILITY INFORMATION SHOWN ON THIS PLAN IS APPROXIMATE. ROKEH CONSULTING, LLC. MAKES NO CLAIM TO THE ACCURACY OR COMPLETENESS OF UTILITIES SHOWN. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ANY UTILITIES WHETHER THEY BE ABOVE OR BELOW GROUND. PRIOR TO ANY EXCAVATION ON SITE THE CONTRACTOR SHALL CONTACT DIG SAFE AT 1-800-DIG-SAFE

LIST OF ADDITIONAL CONSULTANTS

LAND SURVEYOR JOSEPH M. WICHERT, LLS INC 802 AMHERST STREEET MANCHESTER, NH 03104 Phone: (603) 647-4282

WETLANDS AND SOIL SCIENTIST AARON WECHSLER ASPEN ENVIRONMENTAL 41 LIBERTY HILL ROAD BUILDING 2, UNIT 201 HENNIKER, NH 03242 603) 848-5606



UNDER THE PROVISIONS OF RSA 674: 35 & 673: 36			
CHICHESTER PLANNING BOARD IN ACCORDANCE OF A MAJORITY VOTE OF THE BOARD APPROVED			
CHAIR			
SECRETARY DATE SIGNED:			

Developer Mal-Mar, LLC 20 Summit Avenue, Derry, NH

COVER SHEET SITE PLAN TAX PARCEL 4 LOT 150C & E DOVER ROAD CHICHESTER, MERRIMACK COUNTY, NEW HAMPSHIRE

REVISIONS				
DATE	DESCRIPTION	DWN BY	CK BY	
03/05/20 03/13/20 04/02/20	ADDRESS NHDES AOT COMMENTS ADDRESS NHDES AOT COMMENTS ADDRESS NHDOT AND TOWN COMMENTS	JR JR JR	JR JR JR	

Rokeh Consulting, LLC 89 KING ROAD, CHICHESTER, NH PH: 603-387-8688

SCALE: NTS DATE: OCTOBER 2, 2019 DR. BY: JR CK. BY: JR JOB NO. _____ SHEET NO. 1 OF 10

